

PURPOSE

THRIFT KOTE is a specially designed form release that provides:

1. Improved release of formwork.
2. Reduced buildup on forms.
3. Reduced cleaning of formwork.
4. No residue, stain or discoloration.

DESCRIPTION

THRIFT KOTE is a chemically reactive, diesel free form release in a hydrocarbon carrier. It is water insoluble, containing no paraffin or silicone.

THRIFT KOTE is available in standard and cherry-scented formulations. The cherry scent disguises the odor and reduces worker complaints, especially in confined areas.

PACKAGING

THRIFT KOTE is packaged in 275 gallon (1040.9 L) totes, 55 gallon (208.2 L) drums and 5 gallon (18.9 L) pails.

STANDARDS

THRIFT KOTE meets V.O.C. emission requirements for form releases (EPA limit 450 g/L).

THRIFT KOTE meets Corps of Engineers CW-03101, Section 2.1.2 and conforms to guidelines of ACI 301 and 303.

APPLICATION

Storage: To prevent contamination, containers should be tightly closed and properly stored. Prevent accumulation of water, dirt or other residue on covers.

Preparation: Formwork surfaces should be clean and dry before applying THRIFT KOTE. For best results, remove any dirt, rust, scale or concrete before application.

Formwork surfaces that have been previously treated with a neutral form release should be cleaned with detergent and warm water, then thoroughly rinsed and dried before using THRIFT KOTE.

Coverage: Spray application of THRIFT KOTE is recommended with uniform coverage per gallon as follows:

Steel, Plastic	1500 ft ²	(36.8 m ² /L)
MDO Plywood	1200 ft ²	(29.4 m ² /L)
BB Grade Plyform	800 ft ²	(19.6 m ² /L)
Dimensional Lumber	800 ft ²	(19.6 m ² /L)

Actual application rates depend on the type of forming surface. For example, plywood will absorb more material than steel formwork.

THRIFT KOTE may also be applied by roller or brush, but prevent build-up and overapplication.

Excess material or "puddles" should be removed with a squeegee and absorbent rags.

When properly applied, THRIFT KOTE will not leave any residue or stain on the concrete. Formed concrete surfaces will accept subsequent coatings.

Unusual applications or conditions may require the technical assistance of a Symons representative.

LIMITATIONS

THRIFT KOTE is not recommended for untreated Masonite, untreated paper, Styrofoam or form surfaces that exceed 160°F (71°C).

THRIFT KOTE should not be applied to reinforcing steel.

THRIFT KOTE overapplication may cause concrete "dusting."

THRIFT KOTE should not be used as a bondbreaker.

SHELF LIFE

Shelf life of THRIFT KOTE in properly stored containers is one year.

PRECAUTIONS

It is mandatory to take the following precautions to protect workers and the public:

1. KEEP OUT OF THE REACH OF CHILDREN.
2. This product is combustible. Keep away from excessive heat and open flame.
3. Avoid inhalation of vapors. Ensure adequate ventilation.
4. Avoid contact with skin. Protective clothing is recommended. Contact areas should be thoroughly washed with soap and water.
5. Avoid contact with eyes. Protective goggles are recommended in case of splashing. Flush eyes with water if contact occurs.
6. Avoid ingestion of material. If ingestion occurs, contact a poison center or physician.

Additional precautions, safety information and first aid treatments are contained in the Material Safety Data Sheet.

WARRANTY

Symons warrants, for 12 months from the date of manufacture, or for the duration of the published product shelf life, whichever is less, that at the time of shipment by Symons, the product is free of manufacturing defects and conforms to Symons' published specifications in force on the date of acceptance by Symons of the order. Symons shall only be liable under this warranty if the material has been applied, used, and stored in accordance with Symons instructions in this technical data sheet.

The purchaser must examine the product when received and promptly notify Symons in writing of any nonconformity before the product is used, or no later than 30 days after such nonconformity is first discovered. If Symons, in its sole discretion, determines that the product breached the above warranty, it will, in its sole discretion, replace the nonconforming product, refund the purchase price or issue a credit. This is the sole and exclusive remedy for breach of this warranty.

Only a Symons officer is authorized to modify this warranty. The sales information on the Symons website and received by the customer during the sales process does not supersede this warranty and the specifications of the product in force on the date of sale. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM, TRADE OR OTHERWISE.

LIMITATION OF LIABILITY

Symons shall not be liable, in contract or in tort (including, without limitation, negligence, strict liability or otherwise) for loss of sales, revenues or profits; cost of capital or funds; business interruption or cost of downtime, loss of use, damage to or loss of use of other property (real or personal); failure to realize expected savings; frustration of economic or business expectations; claims by third parties (other than for bodily injuries), or economic losses of any kind; or for any special, incidental, indirect, consequential, special, punitive or exemplary damages arising in any way out of the performance of, or failure to perform, this Agreement, even if Symons could foresee or has been advised of the possibility of such damages. The Parties expressly agree that these limitations on damages are allocations of risk constituting, in part, the consideration for this agreement, and also that such limitations shall survive the determination of any court of competent jurisdiction that any remedy provided in these terms or available at law fails of its essential purpose.

MANUFACTURER

Symons
2400 Arthur Avenue
Elk Grove Village, IL 60007

General: 847-298-3200
FAX: 847-635-9287

© 2007

www.symons.com
info@symons.com

Technical: 877-854-0643
Fax: 913-279-4806