



MATERIAL SAFETY DATA SHEET

I. Product and Company Identification

Product: MASCOBOND LO MOD, COMPONENT B **Revision Date:** 03/29/2011

Manufacturer: Masons Supply Company (MASCO)
2637 SE 12th Avenue
Portland, OR 97202
TEL (503) 234-4321
FAX (503) 234-5606

II. Hazards Identification

Emergency Overview

Amber. Liquid. May cause slight irritation to the respiratory system. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

Acute Potential Health Effects/Routes of Entry

Inhalation: May cause slight irritation to the respiratory system.

Eyes: Vapors or liquid may cause tearing, blurred vision, severe irritation, and possible chemical burns.

Ingestion: May cause gastrointestinal irritation, nausea, and vomiting. May cause chemical burns to stomach, mouth, nose, and throat.

Skin: May cause itching, reddening, inflammation. May cause severe burns, blistering and skin damage. May cause sensitization resulting in irritation, itching and redness. May cause a rash.

Aggravated Medical Conditions:

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects:

May cause sensitization by contact. Prolonged skin contact may cause irritation, burns or dermatitis. Repeated overexposure to vapors and/or material may injure liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. May aggravate persons sensitized to amines. Diethylenetriamine is a skin and eye irritant. Prolonged and repeated exposure can cause skin sensitization, dermatitis, asthma. Repeated inhalation of nonyl phenol may cause lung damage. Repeated skin contact with nonyl phenol may cause skin irritation and dermatitis. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

III. Product Composition

Chemical Name	CAS. #	Weight %
4-Nonylphenol	84852-15-3	40.0 - 70.0
Epoxy curing agent	NJ TSRN# 51721300-5477P	15.0 - 40.0
Continued on next page...		

III. Product Composition (Continued)

Chemical Name	CAS. #	Weight %
Poly(oxypropylene) diamine	9046-10-0	10.0 - 30.0
Diethylenetriamine	111-40-0	7.0 - 13.0
Bisphenol A	80-05-7	3.0 - 7.0
Tris(dimethylaminomethyl)phenol	90-72-2	3.0 - 7.0

IV. First Aid Measures

Get immediate medical attention for any significant overexposure.

Inhalation: Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

Eye Contact: Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.

Skin Contact: Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.

Ingestion: Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

V. Fire Fighting Measures

Flash Point: >200° F, > 93° C.

Method: Setaflash Closed Cup.

Lower explosion limit: Not available.

Upper explosion limit: Not available.

Autoignition temperature: Not available.

Extinguishing media: If water fog is ineffective, use carbon dioxide, dry chemical or foam.

Hazardous combustion products: Carbon monoxide and carbon dioxide can form. Smoke, fumes. Nitrogen oxides can form.

Protective equipment for firefighters: Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).

Fire and explosion conditions: Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Vapor concentrations in enclosed areas may ignite explosively. Empty containers may contain ignitable vapors.

VI. Accidental Release Measures

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

VII. Handling and Storage

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not smoke, weld, generate sparks, or use flame near container. Do not use in confined or poorly ventilated areas. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store under dry warehouse conditions away from heat and all ignition sources.

VIII. Exposure Controls / Personal Protection

Personal protection equipment

Respiratory protection: Wear NIOSH/MSHA approved vapor respirator with appropriate cartridge when the vapor concentration is expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.

Hand protection: Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.

Eye protection: Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.

Skin and body protection: Prevent contact with shoes and clothing. Use rubber apron and overshoes.

Protective measures: Inspect and replace equipment at regular intervals. Use professional judgment in the selection, care, and use.

Engineering measures: Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS. #	Regulation	Limit	Form
Diethylenetriamine	111-40-0	ACGIH TWA	1 ppm	

IX. Physical and Chemical Properties

Form: Liquid
 Color: Amber
 Odor: Amine
 pH: Not available.
 Vapour pressure: Not available.
 Vapor Density: Heavier than air.
 Melting point/range: Not available.
 Freezing point: Not available.
 Boiling point/range: Not available.

Continued on next page...

IX. Physical and Chemical Properties (Continued)

Water solubility:	Negligible
Specific Gravity:	1.20
% Volatile Weight:	47.4 %

X. Reactivity/Stability

Substances to avoid:	Oxidizing agents. Epoxies. Isocyanates. Acids.
Stability:	Material is stable under normal storage, handling, and use.
Hazardous polymerization:	Will not occur under normal conditions.

XI. Toxicological Information

Diethylenetriamine, CAS-No.: 111-40-0 Acute oral toxicity (LD-50 oral)	1,080 mg/kg (Rat) 2,330 mg/kg (Rat)
Bisphenol A, CAS-No.: 80-05-7 Acute oral toxicity (LD-50 oral)	3,300 mg/kg (Rat) 4,100 mg/kg (Rat) 3,300 mg/kg (Rat) 5,280 mg/kg (Mouse) 4,100 mg/kg (Mouse) 2,500 mg/kg (Mouse) 4,100 mg/kg (Mouse) 5,280 mg/kg (Mouse) 4,100 mg/kg (Rat) 2,500 mg/kg (Mouse)

XII. Ecological Information

No Data Available

XIII. Disposal Considerations

Disposal Method:	Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.
------------------	--

XIV. Transportation/Shipping Data

TDG / DOT Shipping Description:

CORROSIVE LIQUID, N.O.S. (Aliphatic Amine), 8, UN1760, PG III

XV. Regulatory Information

North American Inventories:

All components are listed or exempt from the TSCA inventory.
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

Continued on next page...

XV. Regulatory Information (Continued)

U.S. Federal Regulations:

SARA 313 Components: Bisphenol A 80-05-7

SARA 311/312 Hazards: Acute Health Hazard

OSHA Hazardous Components:

Diethylenetriamine 111-40-0

Bisphenol A 80-05-7

OSHA Status: Considered Irritant
hazardous based on the Corrosive
following criteria:

OSHA Flammability: Not Regulated

Regulatory VOC (less water and exempt solvent): 569 g/l
VOC Method 310: 47 %

U.S. State Regulations:

MASS RTK Components: Diethylenetriamine 111-40-0
Bisphenol A 80-05-7

Penn RTK Components: 4-Nonylphenol 84852-15-3
Epoxy curing agent NJ TSRN# 51721300-5477P
Poly(oxypropylene) diamine 9046-10-0
Diethylenetriamine 111-40-0
Bisphenol A 80-05-7

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

None known.

XVI. Other Information

HMIS Rating:

Health	2
Flammability	1
Reactivity	1
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

Further Information

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

LEGEND

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response,
Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and
Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials
Information System