

Version 1.1 Print Date 07/13/2007

REVISION DATE: 04/26/2007

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : SPEED CRETE RED LINE 50# BAG

Product code : TR5101650

COMPANY : Euclid Chemical Company

19218 Redwood Road Cleveland, OH 44110

Telephone : 1-800-321-7628

Emergency Phone: : U.S. only: 1-800-255-3924

International Users Call Collect: 1-813-248-0585

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Gray. Powder. Dust may irritate nose and throat. Dust irritating to the respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : Dust may irritate nose and throat. Dust irritating to the respiratory tract.

Eyes : Direct contact may cause severe irritation. May cause mechanical irritation or abrasion,

and possible chemical burns. May cause temporary injury.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal

irritation, nausea, and vomiting.

Skin : May cause severe irritation. May cause dryness, cracking, irritation, and chemical burns.

May produce cement dermatitis due to primary irritation from alkaline, hydroscopic and

abrasive properties.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Portland cement	65997-15-1	40.0 - 70.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	15.0 - 40.0
Calcium Salt	26499-65-0	10.0 - 30.0
Clay	NJ TSRN# 51721300-5165P	5.0 - 10.0
Calcium salt	7778-18-9	1.0 - 5.0



Version 1.1 Print Date 07/13/2007

REVISION DATE: 04/26/2007

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get

medical attention.

Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical

attention immediately.

Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other

disorders develop, get medical attention immediately.

Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control

Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point : Not available.

Method : Not available.

Lower explosion limit : Not available.

Upper explosion limit : Not available.

Autoignition temperature : Not available.

Extinguishing media : This product is not expected to burn under normal conditions of use. Use

that which is appropriate to the surroundings.

Hazardous combustion

products

Not available.

Protective equipment for

firefighters

Not applicable. Product is not expected to burn.

Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES


Use appropriate protective equipment. Avoid contact with material. Dampen material with water to control dusting. Scoop up and transfer to appropriate container for disposal. Flush spill area with water.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of dust and contact with skin and eyes. Clean hands thoroughly after handling. Precautions also apply to emptied containers. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store in sealed containers in a cool, dry, ventilated warehouse location.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment





TR5101650

SPEED CRETE RED LINE 50# BAG

Version 1.1 Print Date 07/13/2007

REVISION DATE: 04/26/2007

Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved dust respirator

where airborne concentrations are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.

Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to

reduce exposure.

Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face

shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily

available.

Skin and body protection : Prevent contact with shoes and clothing.

Protective measures : Use professional judgment in the selection, care, and use. Wear gloves, head

coverings and full body clothing as necessary to prevent skin irritation. Washable or disposable clothing may be used. Do not take unwashed clothing home. Work clothes should be washed separately from other clothing and the washing machine rinsed thoroughly following use. Inform the launderer of the proper procedures. Store work clothes and street clothes

separately to prevent contamination.

Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed

areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Portland cement	65997-15-1	ACGIH TWA:	10 mg/m3	
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
Crystalline Silica (Quartz)/	14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable.
Silica Sand		OSHA TWA:	0.3 mg/m3	Total dust.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction.
Calcium Salt	26499-65-0	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	10 mg/m3	
		ACGIH TWA:	3 mg/m3	Respirable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	10 mg/m3	Inhalable fraction.
		ACGIH TWA:	10 mg/m3	Inhalable fraction.
Clay	1332-58-7	ACGIH TWA:	2 mg/m3	Respirable fraction.
·		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
		OSHA TWA:	15 mg/m3	Total dust.



Version 1.1 Print Date 07/13/2007

REVISION DATE: 04/26/2007

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Calcium salt	7778-18-9	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA: ACGIH TWA:	10 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3 10 mg/m3	Respirable fraction. Total dust. Total dust. Respirable fraction. Inhalable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form : Powder Color : Gray Odor : Slight

pH : Not available.

Vapour pressure : Not available.

Vapor density : Not available.

Melting point/range : Not available.

Freezing point : Not available.

Boiling point/range : Not available.

Water solubility : Slightly soluble

Specific Gravity : 3.5 % Volatile Weight : 0.0 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Not Applicable.

Stability : Material is stable under normal storage, handling, and use.

Hazardous polymerization : Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No Data Available

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Not regulated under RCRA. Dispose of in compliance with state and local regulations.

Do not incinerate.



Version 1.1 Print Date 07/13/2007

REVISION DATE: 04/26/2007

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:

NOT REGULATED

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.

One or more components are listed on the NDSL.

U.S. Federal Regulations:

SARA 313 Components • None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

OSHA Hazardous Components:

Portland cement 65997-15-1 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Calcium Salt 26499-65-0

Clay NJ TSRN# 51721300-5165P

Calcium salt 7778-18-9

OSHA Status: Considered : Irritant hazardous based on the Carcinogen

following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and

exempt solvent)

: 0 g/l

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen: Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

U.S. State Regulations:

NJ RTK Components

MASS RTK Components : Portland cement 65997-15-1

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7 Calcium Salt 26499-65-0 Calcium salt 7778-18-9

Penn RTK Components : Portland cement 65997-15-1

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7 Calcium Salt 26499-65-0

Clay NJ TSRN# 51721300-5165P

65997-15-1

Calcium salt 7778-18-9

Portland cement

Material Safety Data Sheet



SPEED CRETE RED LINE 50# BAG

Version 1.1 Print Date 07/13/2007

REVISION DATE: 04/26/2007

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7 Calcium Salt 26499-65-0

Clay NJ TSRN# 51721300-5165P

Calcium salt 7778-18-9

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other

reproductive harm:

14808-60-7 Crystalline Silica (Quartz)/ Silica Sand

SECTION 16 - OTHER INFORMATION

HMIS Rating:

Health	1	0 = Minimum
Flammability	0	1 = Slight
Reactivity	0	2 = Moderate
PPE		3 = Serious
		4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System