

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/28/2003

Reviewed on 01/28/2003

1 Identification of substance

· **Product details**

· **Trade name:** Masons Cure & Seal 25% UV FD

· **Article number:** 84-273567

· **Manufacturer/Supplier:**

Masons Supply Company
2637 SE 12th Avenue
Portland, OR 97202

Tel.: (800) 537-3407

· **Information department:** Environmental, Health, and Safety department.

2 Composition/Data on components

· **Chemical characterization**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

1330-20-7	xylene	25-50%
25551-13-7	Trimethylbenzene	10-25%
100-41-4	ethylbenzene	10-25%
95-63-6	1,2,4-trimethylbenzene	£ 10%
98-82-8	cumene	£ 1%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

· **Hazard description:**

Harmful

· **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to internationally acknowledged calculation procedures using the latest valid versions.

Flammable.

Harmful by inhalation and in contact with skin.

Irritating to skin.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

(Contd. on page 2)

- USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/28/2003

Reviewed on 01/28/2003

Trade name: *Masons Cure & Seal 25% UV FD*

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

4 First aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

· **After eye contact:**

*Rinse opened eye for several minutes under running water. Then consult a doctor.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.*

· **After swallowing:** *If symptoms persist consult doctor.*

5 Fire fighting measures

· **Suitable extinguishing agents:** *CO₂, sand, extinguishing powder. Do not use water.*

· **For safety reasons unsuitable extinguishing agents:**

Water

Water with full jet

· **Protective equipment:** *Mouth respiratory protective device.*

6 Accidental release measures

· **Person-related safety precautions:** *Wear protective equipment. Keep unprotected persons away.*

· **Measures for environmental protection:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage

· **Handling:**

· **Information for safe handling:** *Ensure good ventilation/exhaustion at the workplace.*

(Contd. on page 3)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/28/2003

Reviewed on 01/28/2003

Trade name: *Masons Cure & Seal 25% UV FD*

(Contd. of page 2)

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· **Storage:**

- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

1330-20-7 xylene

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm (o-, m-, & p-isomers)
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm
BEI	

25551-13-7 Trimethylbenzene

REL	125 mg/m ³ , 25 ppm (1,2,3-; 1,2,4-; and 1,3,5-isomers)
-----	---

100-41-4 ethylbenzene

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 543 mg/m ³ , 125 ppm Long-term value: 434 mg/m ³ , 100 ppm
BEI	

- **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests, no recommendation to the glove material can be given for the product.

(Contd. on page 4)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/28/2003

Reviewed on 01/28/2003

Trade name: *Masons Cure & Seal 25% UV FD*

(Contd. of page 3)

Select the glove material upon consideration of the penetration times, rates of diffusion and the degradation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 137°C (279°F)

· **Flash point:** 27°C (81°F)

· **Ignition temperature:** 430.0°C (806°F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:	1.0 Vol %
Upper:	7.8 Vol %

· **Vapor pressure at 20°C (68°F):** 9.5 hPa (7 mm Hg)

· **Density at 20°C (68°F):** 0.917 g/cm³

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Solvent content:**

Organic solvents: 60.0 %

· **Solids content:** 26.3 %

10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Dangerous reactions** No dangerous reactions known.

(Contd. on page 5)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/28/2003

Reviewed on 01/28/2003

Trade name: *Masons Cure & Seal 25% UV FD*

(Contd. of page 4)

· **Dangerous products of decomposition:** *No dangerous decomposition products known.*

11 Toxicological information

· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:***1330-20-7 xylene*

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

· **Primary irritant effect:**· **on the skin:** *Irritant to skin and mucous membranes.*· **on the eye:** *No irritating effect.*· **Sensitization:** *No sensitizing effects known.*· **Additional toxicological information:***The product shows the following dangers according to internally approved calculation methods for preparations:**Harmful**Irritant*

12 Ecological information

· **Ecotoxicological effects:**· **Remark:** *Harmful to fish*· **General notes:***Water hazard class 2 (Self-assessment): hazardous for water**Do not allow product to reach ground water, water course or sewage system.**Danger to drinking water if even small quantities leak into the ground.**Harmful to aquatic organisms*

13 Disposal considerations

· **Product:**· **Recommendation:** *Must not be disposed of as normal garbage. Do not allow product to reach sewage system.*· **Uncleaned packagings:**· **Recommendation:** *Disposal must be made according to Federal, State, and Local regulations.*

14 Transport information

· **DOT regulations:**· **Hazard class:**

3

· **Identification number:**

UN1139

· **Packing group:**

III

(Contd. on page 6)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/28/2003

Reviewed on 01/28/2003

Trade name: *Masons Cure & Seal 25% UV FD*

(Contd. of page 5)

- **Proper shipping name (technical name):** COATING SOLUTION
- **Label** 3
- **Limited Quantity Exemption:** Limited Quantity applies for inner packages 1.3 gallons or smaller.
- **U.S. Domestic Ground Shipments:** Same as listed for Standard Shipments above.
- **U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:** Same as listed for Standard Shipments above.

· **Land transport ADR/RID (cross-border):**

- **ADR/RID class:** 3 Flammable liquids
- **Danger code (Kemler):** 30
- **UN-Number:** 1139
- **Packaging group:** III
- **Description of goods:** 1139 COATING SOLUTION

· **Maritime transport IMDG:**

- **IMDG Class:** 3
- **UN Number:** 1139
- **Label** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Propper shipping name:** COATING SOLUTION

· **Air transport ICAO-TI and IATA-DGR:**

- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1139
- **Label** 3
- **Packaging group:** III
- **Propper shipping name:** COATING SOLUTION

15 Regulations

· *Sara*· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

(Contd. on page 7)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/28/2003

Reviewed on 01/28/2003

Trade name: *Masons Cure & Seal 25% UV FD*

(Contd. of page 6)

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

1330-20-7	xylene	25-50%
100-41-4	ethylbenzene	10-25%
95-63-6	1,2,4-trimethylbenzene	£10%
108-88-3	toluene	£1%
98-82-8	cumene	£1%

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to the State of California (Prop. 65) to cause reproductive toxicity:**

108-88-3 | toluene

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	D
100-41-4	ethylbenzene	D
108-88-3	toluene	D
98-82-8	cumene	D;CBD

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
108-88-3	toluene	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
108-88-3	toluene	A4

· **MAK (German Maximum Workplace Concentration)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Harmful

(Contd. on page 8)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 01/28/2003

Reviewed on 01/28/2003

Trade name: Masons Cure & Seal 25% UV FD

(Contd. of page 7)

· Hazard-determining components of labelling:*xylene***· Risk phrases:***Flammable.**Harmful by inhalation and in contact with skin.**Irritating to skin.**Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.***· Safety phrases:***Keep out of the reach of children.**Keep container in a well-ventilated place.**Keep away from food, drink and animal feedingstuffs.**Keep away from sources of ignition - No smoking.**Avoid contact with skin and eyes.**Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.**Wear suitable protective clothing and gloves.**If swallowed, seek medical advice immediately and show this container or label.***· National regulations:****· Water hazard class:** *Water hazard class 2 (Self-assessment): hazardous for water.***16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: *Environmental, Health and Safety department***· Contact:** *Matthew Paquette*