

MASCO FLASH | Cement Based Patching Mortar

Section 1 - Product and Company Identification

Trade Name: MASCO FLASH

Product Code: MR5102650S

Company: Masons Supply Company (MASCO)
2637 SE 12th Avenue
Portland, OR 97202

For more Information Call:
1-800-537-3407

Section 2 - Hazards Identification

Emergency Overview

Gray. Powder. Dust may irritate nose and throat. Dust irritating to the respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects / Routes of Entry

Inhalation: Dust may irritate nose and throat. Dust irritating to the respiratory tract.

Eyes: Direct contact may cause severe irritation. May cause mechanical irritation or abrasion, & possible chemical burns. May cause temporary injury.

Ingestion: May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin: May cause severe irritation. May cause dryness, cracking, irritation, and chemical burns. May produce cement dermatitis due to primary irritation from alkaline, hygroscopic and abrasive properties.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica.

Section 3 - Product Composition

Chemical Name	CAS-No.	Weight %
Portland Cement	65997-15-1	40.0 - 70.0
Crystalline Silica (Quartz) / Silica	14808-60-7	15.0 - 40.0
Sand	26499-65-0	7.0 - 13.0
Clay	NJ TSRN# 51721300-5165P	7.0 - 13.0
Calcium Compounds	7778-18-9	1.0 - 5.0

Section 4 - First Aid Measures

Get immediate medical attention for any significant overexposure.

Inhalation: Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Eye Contact: Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.

Skin Contact: Clean area of contact thoroughly using soap & water. If irritation, rash or other disorders develop, get medical attention immediately.

Ingestion: Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

Section 5 - Fire Fighting Measures

Flash point:	Not available.
Method:	Not available.
Lower explosion limit:	Not available.
Upper explosion limit:	Not available.
Auto ignition temperature:	Not available.
Extinguishing media:	This product is not expected to burn under normal conditions of use. Use that which is appropriate to the surroundings.
Hazardous combustion products:	Not available.
Protective equip. For firefighters:	Not applicable. Product is not expected to burn.
Fire and explosion conditions:	This product not expected to ignite under normal conditions of use.

Section 6 - Accidental Release Measures

Use appropriate protective equipment. Avoid contact with material. Dampen material with water to control dusting. Scoop up and transfer to appropriate container for disposal. Flush spill area with water.

Section 7 - Handling and Storage

Prevent inhalation of dust and contact with skin and eyes. Clean hands thoroughly after handling. Precautions also apply to emptied containers. Personal protective equipment must be worn during maintenance or repair of warehouse location.

Section 8 - Exposure Controls / Personal Protection

Personal Protection Equipment

Respiratory Protection:	Wear appropriate, properly fitted NIOSH/MSHA approved dust respirator where airborne concentrations are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
Hand Protection:	Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
Eye Protection:	Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
Skin and Body Protection:	Prevent contact with shoes and clothing.
Protective Measures:	Use professional judgment in the selection, care, and use. Wear gloves, head coverings and full body clothing as necessary to prevent skin irritation. Washable or disposable clothing may be used. Do not take unwashed clothing home. Work clothes should be washed separately from other clothing and the washing machine rinsed thoroughly following use. Inform the launderer of the proper procedures. Store work clothes and street clothes separately to prevent contamination.
Engineering measures:	Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Portland Cement	65997-15-1	ACGIH TWA: OSHA PEL: OSHA PEL:	10 mg/m3 5 mg/m3 15 mg/m3	Respirable fraction. Total dust.
Crystalline Silica (Quartz) / Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.
Calcium Salt	26499-65-0	OSHA PEL: OSHA PEL: ACGIH TWA: ACGIH TWA: OSHA TWA: OSHA TWA: ACGIH TWA: ACGIH TWA:	5 mg/m3 15 mg/m3 10 mg/m3 3 mg/m3 15 mg/m3 5 mg/m3 10 mg/m3 10 mg/m3	Respirable fraction. Total dust. Respirable particles. Total dust. Respirable fraction. Inhalable fraction. Inhalable fraction.
Clay	1332-58-7	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA:	2 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3 15 mg/m3	Respirable fraction. Respirable fraction. Total dust. Respirable fraction. Total dust.

(Continued on next page...)

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium Salt	7778-18-9	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA: ACGIH TWA:	10 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3 10 mg/m3	Respirable fraction. Total dust. Total dust. Respirable fraction. Inhalable fraction.

Section 9 - Physical and Chemical Properties

Form:	Powder
Color:	Gray
Odor:	None
pH:	Not available.
Vapour pressure:	Not available.
Vapor density:	Not available.
Melting point/range:	Not available
Freezing point:	Not available
Boiling Point / Range:	Not available
Water solubility:	Miscible
Specific Gravity:	3.5
% Volatile Weight:	0.0%

Section 10 - Reactivity / Stability

Substances to avoid:	Not applicable.
Stability:	Material is stable under normal storage, handling, and use.
Hazardous Polymerization:	Will not occur under normal conditions.

Section 11 - Toxicological information

No data available.

Section 12 - Ecological Information

No data available.

Section 13 - Disposal Considerations

Disposal Method: Not regulated under RCRA. Dispose of in compliance with state and local regulations. Do not incinerate.

Section 14 - Transportation / Shipping Data

TDG / DOT Shipping Description:

Not regulated

Section 15 - Regulatory Information

North American Inventories:

All components are listed or exempt from the TSCA inventory. One more components are listed on the NDSL.

U.S. Federal Regulations: None present or none present in regulated quantities
SARA 313 Components

SARA 311/312 Components: Acute Health Hazard
Chronic Health Hazard

OSHA Hazardous Components:
Portland Cement 65997-15-1
Crystalline Silica (quartz)/ Silica Sand 14808-60-7
Calcium Salt 26499-65-0
Clay NJ TSRN#51721300-5165P
Calcium Salt 7778-18-9

OSHA Status:
Considered Hazardous based on the following Irritant
Carcinogen

OSHA Flammability: Not regulated

Regulatory VOC
(less water and exempt solvent): 0 g/l
VOC Method 310: 0%

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:
Crystalline Silica (Quartz) / Silica Sand 14808-60-7

U.S. State Regulations:

MASS RTK Components:	Portland Cement	65997-15-1
	Crystalline Silica (Quartz) / Silica Sand	14808-60-7
	Calcium Salt	26499-65-0
	Calcium Salt	7778-18-9
Penn RTK Components:	Portland Cement	65997-15-1
	Crystalline Silica (Quartz) / Silica Sand	14808-60-7
	Calcium Salt	26499-65-0
	Clay	NJ TSRN# 51721300-5165P
	Calcium Salt	7778-18-9
NJ RTK Components:	Portland Cement	65997-15-1
	Crystalline Silica (Quartz) / Silica Sand	14808-60-7
	Calcium Salt	26499-65-0
	Clay	NJ TSRN# 51721300-5165P
	Calcium Salt	7778-18-9

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects, and/or other reproductive harm:
Crystalline Silica (Quartz) / Silica Sand 14808-60-7

Section 16 - Other Information

HMIS Rating:

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum
1 = Slight
2 = Moderate
3 = Serious
4 = Severe

Further information:

For industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Legend

- ACGIH - American Conference of Governmental Hygienists
- CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act.
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration
- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- RTK - Right To Know
- SARA - Superfund Amendments and Reauthorization Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System

Revised Nov 11/07