

FLOOR

Aluminum back neoprene replaceable squeegee for removing water from concrete or wood surfaces. Neoprene will not mark surface. Uses tapered wood handle.


No.	Size	Wt (lbs)
Neoprene		
TSQ 24	24" Straight	3.00
TSQ 24C	24" Curved	3.00
TSQ 30	30" Straight	4.00
TSQ 30C	30" Curved	4.00
TSQ 36	36" Straight	5.00
TSQ 36C	36" Curved	5.00



SMOOTHER

Designed for smoothing out self leveling floor underlayment products that always need a little help. A must on every job.

No.	Description	Size	Wt (lbs)
TSQ S24	Smoothing Paddle	24" x 4"	3.00



GAUGING RAKE

Gauge rakes or floor coating spreaders for self leveling floor coatings. CAM Floor Topper is generally recommended when thicker material is being spread. It also works best in situations where the substrate surface is smooth. The patented CAM Floor Topper design uses a hardened steel cam with preset depths of $\frac{3}{8}$ " and $\frac{1}{2}$ ".

No.	Description	Size	Wt (lbs)
TSQ CAM	24"	$\frac{3}{8}$ "- $\frac{1}{2}$ "	4.00
CAM SETS			
TSQ CAM1	2 each	$\frac{1}{8}$ "	1.00
TSQ CAM1.5	2 each	$\frac{3}{16}$ "	1.00
TSQ CAM2	2 each	$\frac{1}{4}$ "	1.00
TSQ CAM3	2 each	$\frac{3}{8}$ "	1.00
TSQ CAM4	2 each	$\frac{1}{2}$ "	1.00



SPIKE SHOES

These lightweight shoes are great for working on self leveling floors. Fitted with 1" steel spikes. The flexible center joint gives for extra comfort and two nylon adjustable straps securely hold epoxy show to work boot. One size fits all.

No.	Wt (lbs)
TSQ SHOE	2.50

