


FLOAT SHOE

Float blades are designed to clip-on a finish blade bar. With the blade set in the flat position, high spots are broken down while suction and engine vibration bring grout to the surface, all producing a uniform and level slab.


No.	Size
TTW FL14	10" x 14"
TTW FL18	10" x 18"



FLOAT PAN

Made to fit on non-overlapping riding and walk-behind power trowels. Float pans take the place of regular float blades and are available with slight bevel to keep from digging into concrete. The finish area is slightly smaller than the float pan due to bevel. Special blade slots on the float pan attaches on the trowel. Blade slots are dual directional and can be used on trowels that turn either direction.

No.	Size
TTW FP36S	36" Superflat for 4 blade units
TTW FP46S	46" Superflat for 4 blade units
TTW FP36D	36" Domed for 4 blade units
TTW FP46D	46" Domed for 4 blade units
TTW FPP	Pins Latch



GRINDING STONE

Designed to temporarily convert a power trowel into a floor grinder. Grinding stone holders bolt on to most popular trowels. Not recommended for extended use on a power trowel. Grinding stones are 2" x 2" x 8". These competitively priced stones available in four popular grits: Supercoarse (quickest removal of material), Coarse (for bulk removal of material), Medium (for moderately fast removal), and Fine (ideal for terrazzo floors).

No.	Description	Wt (lbs)
Stones		
TAB S86	Super Coarse, 6 Grit	3.00
TAB S810	Coarse, 10 Grit	3.00
TAB S824	Medium, 24 Grit	3.00
TAB S880	Fine, 80 Grit	3.00
Holder		
TTW H36	Up to 36" Dia. Trowel "Each"	6.00
TTW H46	Over 36" Dia. Trowel "Each"	8.00

