

SECTION 1 CHEMICAL PRODUCT AND IDENTIFICATION

United States Gypsum Company 550 West Adams Street Chicago, Illinois 60661-3637 A Subsidiary of USG Corporation Product Safety: 1 (800) 507-8899 www.usg.com Version Date: January 1, 2014 Version: 8

PRODUCT(S) BEN FRANKLIN® No. 1 Agricultural Gypsum CHEMICAL FAMILY /

GENERAL CATEGORY

Industrial Products, Agricultural

SYNONYMS Gypsum or Calcium Sulfate Dihydrate (CaSO4•2H2O)

SECTION 2 HAZARD IDENTIFICATION

EMERGENCY OVERVIEW:

∆CAUTION!

This product is not expected to produce any unusual hazards during normal use. Exposure to high dust levels may irritate the skin, eyes, nose, throat, or upper respiratory tract. This product does not present an inhalation, ingestion, or contact health hazard unless subjected to operations such as sawing, sanding or machining which result in the generation of airborne particulate. This product contains quartz (crystalline silica) as a naturally occurring contaminant.

POTENTIAL HEALTH EFFECTS (See Section 11 for more information)

ACUTE :	
Inhalation	Exposure to dust generated during the handling or use of the product may cause temporary irritation to eyes, skin, nose, throat, and upper respiratory tract. Persons subjected to large amounts of this dust will be forced to leave area because of nuisance conditions such as coughing, sneezing and nasal irritation. Labored breathing may occur after excessive inhalation. If respiratory symptoms persist, consult physician.
Eyes	Dust can cause temporary mechanical irritation of eyes. If burning, redness, itching, pain or other symptoms persist or develop, consult physician.
Skin	None known.
Ingestion	None known.
CHRONIC:	
Inhalation	Exposures to respirable crystalline silica are not expected during the normal use of this product; however, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer. The development of silicosis may increase the risks of additional health effects. The risk of developing silicosis is dependent upon the exposure intensity and duration.
Eyes	None known.
Skin	None known.
Ingestion	None known.



TARGET ORGANS: Eyes, skin and respiratory system.

PRIMARY ROUTES OF ENTRY: Inhalation, eyes and skin contact.

CARCINOGENICITY CLASSIFICATION OF INGREDIENT(S) All substances listed are associated with the nature of the raw materials used in the manufacture of this product and are not independent components of the product formulation. All substances, if present, are at levels well below regulatory limits. See Section 11: Toxicology Information for detailed information.

MATERIAL	IARC	NTP	ACGIH	CAL- 65
Crystalline silica	1	1	A2	Listed

IARC - International Agency for Research on Cancer: 1- Carcinogenic to humans; 2A – Probably carcinogenic to humans; 2B – Possibly carcinogenic to humans; 3 - Not classifiable as a carcinogen; 4 – Probably not a carcinogen

NTP – National Toxicology Program (Health and Human Services Dept., Public Health Service, NIH/NIEHS): 1-Known to be carcinogen; 2- Anticipated to be carcinogens

ACGIH – American Conference of Governmental Industrial Hygienists: A1 – Confirmed human carcinogen; A2 – Suspected human carcinogen; A3 – Animal carcinogen; A4 - Not classifiable as a carcinogen; A5 – Not suspected as a human carcinogen

CAL-65 – California Proposition 65 "Chemicals known to the State of California to Cause Cancer"

Respirable crystalline silica: IARC: Group 1 carcinogen, NTP: Known human carcinogen. The weight percent of crystalline silica given represents total quartz and not the respirable fraction. The weight percent of respirable silica has not been measured in this product.

Food and Drug Administration [CFR Title 21, v.3, sec 184.1230] – Calcium Sulfate is Generally Recognized as Safe (GRAS).

POTENTIAL ENVIRONMENTAL EFFECTS: Toxicity studies of gypsum performed with fish, aquatic invertebrates and aquatic plants showed no toxic effect. (See Section 12 for more information.)

SECTION 3 COMPOSITION, INFORMATION ON INGREDIENTS

MATERIAL	WT%	CAS #
Gypsum, Anhydrite or Gypsum/Anhydrite Blend	>85	13397-24-5/14798-04-0
Naturally Occuring Minerals	<15	See Note below^
Crystalline Silica	<5	14808-60-7^

All ingredients of this product are included in the U.S. Environmental Protection Agency's Toxic Substances Control Act Chemical Substance Inventory and the Canadian Domestic Substances List (DSL).

^Commercial deposits of gypsum may be almost pure or contain variable amounts of impurities typically as limestone, dolomite, clay, anhydrite, and soluble salts of potassium, sodium, and magnesium. Anhydrite may occur as either primary or secondary minerals in a deposit, depending on its geological history.^The weight percent for silica represents total quartz and not the respirable fraction.

SECTION 4 FIRST AID MEASURES

FIRST AID PROCEDURES

Inhalation

Remove to fresh air. Leave the area of exposure and remain away until coughing and other symptoms subside. Other measures are usually not necessary, however if conditions warrant, contact physician.



Eyes	In case of contact, do not rub or scratch your eyes. To prevent mechanical irritation, flush thoroughly with water for 15 minutes. If irritation persists, consult physician.
Skin	Wash with mild soap and water. If irritation persists, consult physician.
Ingestion	This product is not intended to be ingested or eaten. If gastric disturbance occurs, call physician.

MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED: Pre-existing upper respiratory and lung diseases such as, but not limited to, bronchitis, emphysema and asthma. Pre-existing skin diseases such as, but not limited to, rashes and dermatitis.

NOTES TO PHYSICIAN: Treatment should be directed at the control of symptoms and the clinical condition.

SECTION 5 FIRE FIGHTING MEASURES

General Fire Hazards		None known				
Extinguishing Media		Water or use extinguishing media appropriate for surrounding fire.				
Special Fire Fighting Procedure	s	Wear appropriate personal protective equipment. See section 8.				
Unusual Fire/ Explosion Hazard	s	None known				
Hazardous Combustion Produc	ts	Above 1450° C - decomposes to calcium oxide (CaO) and sulfur dioxid (SO2).				
Flash Point	Not I	Determined	Auto Ignition	Not Applicable		
Method Used	Not /	Applicable	Flammability			
Upper Flammable Limit (UFL)	Not I	Determined Classification		Not Applicable		
Lower Flammable Limit (LFL)) Not Determined		Rate of Burning	Not Applicable		

SECTION 6 ACCIDENTAL RELEASE MEASURES

CONTAINMENT: No special precautions. Wear appropriate personal protective equipment. See section 8.

CLEAN-UP: Use normal clean up procedures. No special precautions.

DISPOSAL: Follow all local, state, provincial and federal regulations. Never discharge large releases directly into sewers or surface waters.

SECTION 7 HANDLING AND STORAGE

HANDLING: Avoid dust contact with eyes and skin. Wear the appropriate eye and skin protection against dust (See Section 8). Minimize dust generation and accumulation. Avoid breathing dust. Wear the appropriate respiratory protection against dust in poorly ventilated areas and if TLV is exceeded (see Sections 2 and 8). Use good safety and industrial hygiene practices.

STORAGE: Store in a cool, dry, ventilated area away from sources of heat, moisture and incompatibilities (see Section 10).

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

MATERIAL	-	WT%	TLV (mg/m ³)	PEL(mg/m ³)
Gypsum, A	Anhydrite or Gypsum/Anhydrite Blend	>85	10	15(T)/5(R)
-	y Occuring Minerals	<15	(NE)	(NE)
Crystall	ine Silica	<5	0.025(R)	0.1(R)
. ,	(Du)-Dust; (M)-Mist er million; f/cc-fiber per cubic centimeter; mppcf- mil	lion particles pe	er cubic foot	
	RING CONTROLS: Provide ventilation sufficient to co ust, use ventilation to keep dust concentrations below			
airborne du	RING CONTROLS: Provide ventilation sufficient to co ust, use ventilation to keep dust concentrations below is inadequate, use process enclosures, local exhaust	permissible exp	oosure limits. Where	e general
airborne du ventilation i	st, use ventilation to keep dust concentrations below	permissible exp	oosure limits. Where	e general
airborne du ventilation i dust levels	ist, use ventilation to keep dust concentrations below is inadequate, use process enclosures, local exhaust below permissible exposure limits.	permissible exp ventilation, or c	oosure limits. When other engineering co	e general ntrols to control
airborne du ventilation i dust levels RESPIRAT	ist, use ventilation to keep dust concentrations below is inadequate, use process enclosures, local exhaust below permissible exposure limits. TORY PROTECTION: Wear a NIOSH/MSHA-approve	permissible exp ventilation, or o d respirator eq	oosure limits. When other engineering co uipped with particula	e general ntrols to control ate cartridges whe
airborne du ventilation i dust levels RESPIRAT dusty in poo	ist, use ventilation to keep dust concentrations below is inadequate, use process enclosures, local exhaust below permissible exposure limits. TORY PROTECTION: Wear a NIOSH/MSHA-approve orly ventilated areas, and if TLV is exceeded. A respi	permissible exp ventilation, or o d respirator eq ratory program	oosure limits. When other engineering co uipped with particula that meets OSHA's	e general ntrols to control ate cartridges whe 29 CFR 1910.134
airborne du ventilation i dust levels RESPIRAT dusty in poo and ANSI Z	ist, use ventilation to keep dust concentrations below is inadequate, use process enclosures, local exhaust below permissible exposure limits. TORY PROTECTION: Wear a NIOSH/MSHA-approve	permissible exp ventilation, or o d respirator eq ratory program blace conditions	bosure limits. When other engineering co uipped with particula that meets OSHA's warrant a respirato	e general ntrols to control ate cartridges whe 29 CFR 1910.134 r's use. If
airborne du ventilation i dust levels RESPIRAT dusty in poo and ANSI Z	ist, use ventilation to keep dust concentrations below is inadequate, use process enclosures, local exhaust below permissible exposure limits. TORY PROTECTION: Wear a NIOSH/MSHA-approve orly ventilated areas, and if TLV is exceeded. A respi 288.2 requirements must be followed whenever workp	permissible exp ventilation, or o d respirator eq ratory program blace conditions	bosure limits. When other engineering co uipped with particula that meets OSHA's warrant a respirato	e general ntrols to control ate cartridges whe 29 CFR 1910.13 r's use. If
airborne du ventilation i dust levels RESPIRAT dusty in poo and ANSI Z engineering	ist, use ventilation to keep dust concentrations below is inadequate, use process enclosures, local exhaust below permissible exposure limits. TORY PROTECTION: Wear a NIOSH/MSHA-approve orly ventilated areas, and if TLV is exceeded. A respi 288.2 requirements must be followed whenever workp	permissible exp ventilation, or o d respirator eq ratory program blace conditions	bosure limits. When other engineering co uipped with particula that meets OSHA's warrant a respirato	e general ntrols to control ate cartridges whe 29 CFR 1910.13 r's use. If
airborne du ventilation i dust levels RESPIRAT dusty in por and ANSI Z engineering	 ist, use ventilation to keep dust concentrations below is inadequate, use process enclosures, local exhaust below permissible exposure limits. TORY PROTECTION: Wear a NIOSH/MSHA-approve orly ventilated areas, and if TLV is exceeded. A respine 288.2 requirements must be followed whenever workping controls are not possible, wear a properly fitted NIO 	permissible exp ventilation, or o d respirator eq ratory program place conditions SH/MSHA-app	bosure limits. When other engineering co uipped with particula that meets OSHA's warrant a respirato roved particulate res	e general ntrols to control ate cartridges whe 29 CFR 1910.134 r's use. If

General Selection of Personal Protective Equipment will depend on environmental working conditions and operations.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	White to off-white	Vapor Density (Air = 1)	Not Applicable
Odor	Low to no odor	Specific Gravity (H ₂ O = 1)	~2.32 (Gypsum)
Odor Threshold	Not Determined	Solubility in water (g/100g)	~ 21 (Gypsum)
Physical State	Solid/ Powder	Partition Coefficient	Not Determined
pH @ 25 º C	~7	Auto-ignition Temp	Not Determined
Melting Point	Not Applicable	Decomposition Temp	2642°F/1450°C
Freezing Point	Not Applicable	Viscosity	Not Applicable
Boiling Point	Not Applicable	Particle Size	Varies



Flash Point	Not Determined	Bulk Density	~ 45-150 lb/ft3 / 0.7 - 2.5 kg/m3
Evaporation Rate (BuAc = 1)	Not Applicable	Molecular Weight	~172 g/mole
Upper Flammable Limit (UFL)	Not Determined	VOC Content	Zero g/L
Lower Flammable Limit (LFL)	Not Determined	Percent Volatile	Zero
Vapor Pressure (mm Hg)	Not Applicable		

SECTION 10 CHEMICAL STABILITY AND REACTIVITY

STABILITY Stable. CONDITIONS TO AVOID Contact with incompatibles (see below).	
CONDITIONS TO AVOID Contact with incompatibles (see below).	
INCOMPATIBILITY None known.	
HAZARDOUS POLYMERIZATION None known.	
HAZARDOUS DECOMPOSITION Above 1450° C - calcium oxide (CaO) and sulfur dioxide (SaC)	02).

SECTION 11 TOXICOLOGICAL INFORMATION

ACUTE EFFECTS: The acute oral toxicity study [OECD TG 420] of calcium sulfate dihydrate showed that this chemical did not cause any changes even at 2,000 mg/kg b.w. Therefore, the oral LD50 value was more than 2,000-mg/kg b.w. for female rats. Gypsum paste applied experimentally to the eyes of rabbits was not an irritant. Gypsum dust particulate has shown an irritant action on mucous membranes of the respiratory tract and eyes. The sulfate ion has caused gastro-intestinal disturbance in humans following large oral doses. Limited studies involving the repeated inhalation of an (unspecified) calcium sulfate failed to identify any particular target organs in monkeys, rats and hamsters. No evidence of mutagenicity was found in Ames bacterial tests.

CHRONIC EFFECTS / CARCINOGENICITY:

Crystalline Silica: Exposures to respirable crystalline silica are not expected during the normal use of this product; however, actual levels must be determined by workplace hygiene testing. The weight percent of respirable crystalline silica may not have been measured in this product. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer. The development of silicosis may increase the risks of additional health effects. Smoking in combination with silica exposures increases the risk of cancer. The risk of developing silicosis is dependent upon the exposure intensity and duration.

In June, 1997, IARC classified crystalline silica (quartz and cristobalite) as a human carcinogen. In making the overall evaluation, the IARC Working Group noted that carcinogenicity in humans was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs.

IARC states that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1).

SECTION 12 ECOLOGICAL INFORMATION



ENVIRONMENTAL TOXICITY: This product has no known adverse effect on ecology. Toxicity studies of gypsum performed with fish, aquatic invertebrates and aquatic plants showed no toxic effect.

Ecotoxicity value

Not determined.

SECTION 13 DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of material in accordance with federal, state, and local regulations. Never discharge directly into sewers or surface waters. Consult with environmental regulatory agencies for guidance on acceptable disposal practices.

SECTION 14 TRANSPORT INFORMATION

U.S. DOT INFORMATION: Not a hazardous material per DOT shipping requirements. Not classified or regulated.

Shipping Name	Same as product name.
Hazard Class	Not classified.
UN/NA #	None. Not classified.
Packing Group	None.
Label (s) Required	Not applicable.
GGVSec/MDG-Code	Not classified.
ICAO/IATA-DGR	Not applicable.
RID/ADR	None.
ADNR	None.

SECTION 15 REGULATORY INFORMATION

UNITED STATES REGULATIONS

All ingredients of this product are included in the U.S. Environmental Protection Agency's Toxic Substances Control Act Chemical Substance Inventory.

WT%	3 0 2	3 0 4	3 1 3	CERCLA	CAA Sec. 112	RCRA Code
>85	NL	NL	NL	NL	NL	NL
<15	NL	NL	NL	NL	NL	NL
<5	NL	NL	NL	NL	NL	NL
-	>85 <15	WT% 0 2 >85 NL <15	WT% 0 0 0 0 0 0 0 4 0 0 4 0 0 4 0 0 4 0 0 4 0 0 4 0 0 4 0 0 4 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 <th1< th=""> 1 <th1< th=""> <th1< th=""></th1<></th1<></th1<>	WT% 0 0 1 1 3 >85 NL NL NL NL <15	WT% 0 0 1 1 J <thj< th=""> J <thj< th=""> <thj< th=""></thj<></thj<></thj<>	WT%0 20 41 31 Y Y S1 Y S1 Y S1 Y S1 Y S1 Y S1 Y S1 Y S1 S1 S1 S1 S1 S1 S1 S1



SARA Title III Section 302 (EPCRA) Extremely Hazardous Substances: Threshold Planning Quantity (TPQ)

SARA Title III Section 304 (EPCRA) Extremely Hazardous Substances: Reportable Quantity (RQ)

SARA Title III Section 313 (EPCRA) Toxic Chemicals: X= Subject to reporting under section 313

CERCLA Hazardous Substances: Reportable Quantity (RQ)

CAA Section 112 (r) Regulated Chemicals for Accidental Release Prevention: Threshold Quantities(TQ)

RCRA Hazardous Waste: RCRA hazardous waste code

CANADIAN REGULATIONS

This product has been classified in accordance with the hazard criteria of Controlled Product regulations and the MSDS contains all the information required by the Controlled Products Regulations. All ingredients of this product are included in the Canadian Domestic Substances List (DSL).

MATERIAL	WT%	IDL Item #	WHMIS Classification
Gypsum, Anhydrite or Gypsum/Anhydrite Blend	>85	Not Listed	Not Listed
Naturally Occuring Minerals	<15	Not Listed	Not Listed
Crystalline Silica	<5	1406	D2A

IDL Item#: Canadian Hazardous Products Act - Ingredient Disclosure List Item #

WHMIS Classification: Workplace Hazardous Material Information System

Risk and Safety Phrases defined by European Union Directive 67/548/EEC (Annex III and IV)

R-Phrase(s): R36/37/38

S-Phrase(s): S51 S38 S39

SECTION 16 OTHER INFORMATION

Label Information

∆ CAUTION!

Dust can cause irritation to eyes, skin and respiratory tract. Wear eye, skin and respiratory protection as necessary per working conditions. If eye contact occurs flush with water for 15 minutes. Do not ingest. If ingested, call physician. Product safety information: 800-507-8899 or usg. com. Customer Service: 800 USG-4-YOU (800 874-4968). KEEP OUT OF REACH OF CHILDREN.

INFORMATION FOR HANDLING AND IDENTIFICATION OF CHEMICAL HAZARDS								
						HEALTH * 1	0 = Minimal Hazard	
NFPA Ratings:			HMIS Ratings:			FLAMMABILITY 0	1 = Slight Hazard	
Health:	1		Health:	1			2 = Moderate Hazard	
Fire:	0		Fire:	0		PHYSICAL HAZARD 0	3 = Serious Hazard	
Reactivity:	0	•	Reactivity:	0		PERSONAL PROTECTION	4 = Severe Hazard	
E – Safety glasses, gloves and dust respirator; * - Contains silica								
Key/Legend								
ANSI	American National Standards Institute							

BEN FRANKLIN® No. 1 Agricultural Gypsum

5

ACGIH	American Conference of Governmental Industrial Hygienists				
CAA	Clean Air Act				
CAS	Chemical Abstracts Service (Registry Number)				
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act of 1980				
CFR	Code of Federal Regulations				
DOT	United States Department of Transportation				
DSL	Canadian Domestic Substances List				
EPA	United States Environmental Protection Agency				
EPCRA	Emergency Planning & Community Right-to-know Act				
HMIS	Hazardous Materials Identification System				
IARC	International Agency for Research on Cancer				
MSHA	Mine Safety and Health Administration				
NDSL	Canadian Non-Domestic Substances List				
NFPA	National Fire Protection Association				
NIOSH	National Institute for Occupational Safety and Health				
OSHA	Occupational Health and Safety Administration				
PEL	Permissible Exposure Limit				
PPE	Personal Protection Equipment				
RCRA	Resource Conservation and Recovery Act				
SARA	Superfund Amendments and Reauthorization Act of 1986				
TLV	Threshold Limit Value				
TSCA	Toxic Substances Control Act				
UN/NA#	United Nations/North America number				
WHMIS	Workplace Hazardous Material Information System				
Prepared by:					
Product Safety					
USG Corporation					
550 West Adam					
Chicago, IL 606	61-3637				
material if it is u	contained in this document applies to this specific material as supplied. It may not be valid for this sed in combination with any other materials. It is the user's responsibility to satisfy oneself as to the ompleteness of this information for his/her own particular use.				

END