

SAFETY DATA SHEET

1. Identification

Product identifier BENTOGROUT® Other means of identification Not available. Recommended use Not available.

Workers (and your customers or users in the case of resale) should be informed of the potential **Recommended restrictions**

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

CETCO Company name

2870 Forbs Avenue **Address**

Hoffman Estates, IL 60192

United States

Telephone General Information 800 527-9948

Website http://www.cetco.com/ E-mail safetydata@amcol.com

Emergency phone number

Americas 1.866.519.4752 (US, Canada, Mexico) 1 760 476 3962

2. Hazard(s) identification

Physical hazards Not classified.

Category 4 **Health hazards** Acute toxicity, oral

Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Harmful if swallowed.

Prevention Wash thoroughly after handling. Do not eat, drink or smoke when using this product.

Response If swallowed: Call a poison center/doctor// if you feel unwell. Rinse mouth.

Store away from incompatible materials. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Dispose of contents/container to.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 97% of the mixture consists of component(s) of unknown acute oral toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
SODIUM ACID PYROPHOSPHATE		7758-16-9	3
TRADE SECRET*		Proprietary*	1.5
Other components below reportable lev		95.5	

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Bentonite contains naturally occurring crystalline silica (not listed in Annex I of Directive **Composition comments**

67/548/EEC) in quantities less than 6%. Occupational Exposure Limits for impurities are listed in

Section 8.

4. First-aid measures

Inhalation If symptoms are experienced, remove source of contamination or move victim to fresh air. If the

affected person is not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call

a physician if symptoms develop or persist.

Skin contact

Get medical attention if irritation develops or persists. No special measures required.

Eye contact

Flush eyes immediately with large amounts of water. Get medical attention if irritation develops or

persists

Ingestion

Rinse mouth. If ingestion of a large amount does occur, seek medical attention, IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. No special measures required.

Most important

symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Dry chemical, CO2, water spray or regular foam. Carbon

dioxide (CO2). Use any media suitable for the surrounding fires.

Unsuitable extinguishing

media

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Material can be slippery when wet.

Fire-fighting

equipment/instructions

In the event of fire, cool tanks with water spray.

Specific methods General fire hazards Cool containers exposed to flames with water until well after the fire is out. No unusual fire or explosion hazards noted. This material will not burn.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Material can be slippery when wet. Wear appropriate personal protective equipment. Wear a dust mask if dust is generated above exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Material can be slippery when wet.

Methods and materials for containment and cleaning up

This product is miscible in water. Stop the flow of material, if this is without risk. Collect dust or particulates using a vacuum cleaner with a HEPA filter. Avoid the generation of dusts during clean-up. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. None necessary. Reduce airborne dust and prevent scattering by moistening with water.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. No special environmental precautions required.

7. Handling and storage

Precautions for safe handling

Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not taste or swallow. Avoid prolonged exposure. In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities No special restrictions on storage with other products. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. No special storage conditions required. Store away from incompatible materials (see Section 10 of the SDS). Guard against dust accumulation of this material.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)					
Components	Туре	Value	Form		
TRADE SECRET (CAS Proprietary)	PEL	15 mg/m3	Total particulate.		

Impurities	Туре	Value	Form	
INERT OR NUISANCE DUSTS	PEL	5 mg/m3	Respirable fraction.	
(CAS SEQ250)				
		15 mg/m3	Total dust.	
US. OSHA Table Z-3 (29 C	FR 1910.1000)			
Impurities	Туре	Value	Form	
INERT OR NUISANCE DUSTS (CAS SEQ250)	TWA	5 mg/m3	Respirable fraction.	
		15 mg/m3	Total dust.	
		50 millions of particle	Total dust.	
		15 millions of particle	Respirable fraction.	
QUARTZ (CAS 14808 60-7)	TWA	0.3 mg/m3	Total dust.	
(CAS 14808-60-7)		0.1 mg/m3	Respirable.	
		2.4 millions of particle	Respirable.	
US. ACGIH Threshold Lim	nit Values	•		
Components	Туре	Value	Form	
TRADE SECRET (CAS Proprietary)	TWA	10 mg/m3	Inhalable fraction.	
Impurities	Туре	Value	Form	
INERT OR NUISANCE DUSTS	TWA	3 mg/m3	Respirable particles	
(CAS SEQ250)		10 mg/m3	Inhalable particles.	
QUARTZ	TWA	0.025 mg/m3	Respirable fraction.	
(CAS 14808-60-7)		5.5_5 mg/m5	. toop abio indottorii	
US. NIOSH: Pocket Guide	to Chemical Hazards			
Impurities	Туре	Value	Form	
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.	
ogical limit values	No biological exposure limits noted for the ingr	redient(s).		
osure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.			
ropriate engineering	If material is ground, cut, or used in any operation which may generate dusts, use appropriate local			

Appropriate engineering

controls

If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits. If engineering measures are not sufficient to maintain concentrations of dust particulates below the OEL, suitable respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear dust goggles.

Hand protection For prolonged or repeated skin contact use suitable protective gloves.

Other No special protective equipment required.

Use a particulate filter respirator for particulate concentrations exceeding the Occupational Respiratory protection

Exposure Limit.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Eye wash fountain is recommended. Use good industrial hygiene practices in handling this material.

9. Physical and chemical properties

Appearance

Solid. **Physical state Form** Powder. Various. Color

Material name: BENTOGROUT® 4533 Version #: 12 Revision date: 22-August-2014 Print date: 22-August-2014 Odor None.

Odor threshold Not available.

pH 7 - 9

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not flammable
Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%

Not explosive

Flammability limit - upper

(%)

Not explosive

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure0 hPa estimatedVapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Negligible

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 3.58 g/cm3 estimated

Percent volatile 0 % estimated Specific gravity 3.58 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

Will not occur. Hazardous polymerization does not occur.

Conditions to avoid None known. Contact with incompatible materials.

Incompatible materials None known.

Hazardous decomposition None known.

products

11. Toxicological information

Information on likely routes of exposure

Ingestion Harmful if swallowed.

Inhalation Prolonged inhalation may be harmful.

Skin contact Not available.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the Direct contact with eyes may cause temporary irritation.

physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Test Results Product Species BENTOGROUT® Acute Inhalation LC50 14.5 mg/l/4h Rat Components **Test Results Species** SODIUM ACID PYROPHOSPHATE (CAS 7758-16-9) Acute Inhalation LC50 Rat 0.5801 mg/l/4h Oral LD50 Mouse 2650 mg/kg 1800 mg/kg Rat Other LD50 Mouse 59 mg/kg **Impurities Species Test Results** QUARTZ (CAS 14808-60-7)

Acute Oral

LD50 Rat 500 mg/kg

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Mild irritant to eyes (according to the modified Kay & Calandra criteria) Mild irritant to eyes

(according to the modified Kay & Calandra criteria)

Respiratory or skin sensitization

Respiratory sensitization

Not available.

Skin sensitization

According to the classification criteria of the European Union, the product is not considered as

being a skin irritant.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

irritation

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing

regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable

crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not available.

4533 Version #: 12 Revision date: 22-August-2014 Print date: 22-August-2014

^{*} Estimates for product may be based on additional component data not shown.

Chronic effects

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Prolonged inhalation may be harmful. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

12. Ecological information

Ecotoxicity This material is not expected to be harmful to aquatic life.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations. Material should be recycled if possible.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not available.

the IBC Code

15. Regulatory information

US federal regulations OSHA Process Safety Standard: This material is not known to be hazardous by the OSHA Highly

Hazardous Process Safety Standard, 29 CFR 1910.119.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

> Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely

hazardous substance

Yes

Yes

chemical

SARA 313 (TRI reporting)

SARA 311/312 Hazardous

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US - Pennsylvania RTK - Hazardous Substances: Listed substance

QUARTZ (CAS 14808-60-7)

TRADE SECRET (CAS Proprietary)

US. Massachusetts RTK - Substance List

QUARTZ (CAS 14808-60-7)

TRADE SECRET (CAS Proprietary)

US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Australia	Australian inventory of Chemical Substances (AICS)	163
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

Issue date 22-August-2014 **Revision date** 22-August-2014

Version # 12

Further information This safety datasheet only contains information relating to safety and does not replace any product

information or product specification.

Material name: BENTOGROUT® SDS US

On inventory (yes/no)*

HMIS® ratings Health: 1*

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 1

Flammability: 0 Instability: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

Revision Information

Composition / Information on Ingredients: Ingredients

Material name: BENTOGROUT®
4533 Version #: 12 Revision date: 22-August-2014 Print date: 22-August-2014