

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

1 Identification of substance

- **Product details**
- **Trade name:** AggreGloss™ J25
- **Article number:** 83-69057
- **Application of the substance / the preparation**

- **Manufacturer/Supplier:**

Dayton Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Composition/Data on components

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

1330-20-7	xylene	50-75%
100-41-4	ethylbenzene	10-25%
84-74-2	dibutyl phthalate	≤ 2.5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- **Hazard description:** Not applicable.
- **Information pertaining to particular dangers for man and environment:**
The product has to be labelled due to internationally acknowledged calculation procedures using the latest valid versions.
- **Classification system:**
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	3	Fire = 3
PHYSICAL HAZARD	0	Reactivity = 0

4 First aid measures

- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 2)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

Trade name: AggreGloss™ J25

(Contd. of page 1)

- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Seek medical treatment.

5 Fire fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
Water
Water with full jet
- **Protective equipment:**
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.
Mouth respiratory protective device.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Inform respective authorities in case of seepage into water course or sewage system.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 3)

-USA-

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

Trade name: AggreGloss™ J25

(Contd. of page 2)

· **Components with limit values that require monitoring at the workplace:**

1330-20-7 xylene

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm (o-, m-, & p-isomers)
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

100-41-4 ethylbenzene

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 543 mg/m ³ , 125 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

84-74-2 dibutyl phthalate

PEL	5 mg/m ³
REL	5 mg/m ³
TLV	5 mg/m ³

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

USA

(Contd. on page 4)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

Trade name: AggreGloss™ J25

(Contd. of page 3)

9 Physical and chemical properties

· General Information

Form: Liquid
 Color: According to product specification
 Odor: Characteristic

· Change in condition

Melting point/Melting range: Undetermined.
 Boiling point/Boiling range: 137°C (279°F)

· Flash point: 31°C (88°F)

· Ignition temperature: 430.0°C (806°F)

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 1.0 Vol %
 Upper: 7.8 Vol %

· Vapor pressure at 20°C (68°F): 9.5 hPa (7 mm Hg)

· Density at 20°C (68°F): 0.824 g/cm³

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Solvent content:

Organic solvents: 74.2 %

· Solids content: 23.8 %

· Volatile Organic Compounds: Contains less than 700 g/L.

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Dangerous reactions No dangerous reactions known.

· Dangerous products of decomposition: No dangerous decomposition products known.

11 Toxicological information

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

1330-20-7 xylene

Oral LD50 4300 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

100-41-4 ethylbenzene

Oral LD50 3500 mg/kg (rat)

Dermal LD50 17800 mg/kg (rabbit)

84-74-2 dibutyl phthalate

Oral LD50 8000 mg/kg (rat)

Dermal LD50 20000 mg/kg (rabbit)

(Contd. on page 5)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

Trade name: AggreGloss™ J25

(Contd. of page 4)

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:** No irritating effect known.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

12 Ecological information

- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Product:**
- **Recommendation:**
Must not be disposed of as normal garbage. Do not allow product to reach sewage system.
It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

- **DOT regulations:**



- | | |
|---|---|
| · Hazard class: | 3 |
| · Identification number: | UN1268 |
| · Packing group: | III |
| · Proper shipping name (technical name): | PETROLEUM DISTILLATES, N.O.S. |
| · Label | 3 |
| · Limited Quantity Exemption: | Limited Quantity applies for inner packages 1.3 gallons or smaller. |
| · U.S. Domestic Ground Shipments: | Same as listed for Standard Shipments above. |
| · U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments: | Same as listed for Standard Shipments above. |

(Contd. on page 6)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

Trade name: AggreGloss™ J25

(Contd. of page 5)

· **Emergency Response Guide (ERG) Number:** Not determine· **Land transport ADR/RID (cross-border):**

· **ADR/RID class:** 3 Flammable liquids
 · **Danger code (Kemler):** 30
 · **UN-Number:** 1268
 · **Packaging group:** III
 · **Description of goods:** 1268 PETROLEUM DISTILLATES, N.O.S.

· **Maritime transport IMDG:**

· **IMDG Class:** 3
 · **UN Number:** 1268
 · **Label** 3
 · **Packaging group:** III
 · **EMS Number:** F-E,S-E
 · **Marine pollutant:** No
 · **Propper shipping name:** PETROLEUM DISTILLATES, N.O.S.

· **Air transport ICAO-TI and IATA-DGR:**

· **ICAO/IATA Class:** 3
 · **UN/ID Number:** 1268
 · **Label** 3
 · **Packaging group:** III
 · **Propper shipping name:** PETROLEUM DISTILLATES, N.O.S.

15 Regulations

· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

1330-20-7	xylene	50-75%
100-41-4	ethylbenzene	10-25%
84-74-2	dibutyl phthalate	≤2.5%
108-88-3	toluene	≤1%

(Contd. on page 7)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

Trade name: AggreGloss™ J25

(Contd. of page 6)

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	D
100-41-4	ethylbenzene	D
84-74-2	dibutyl phthalate	D
108-88-3	toluene	D

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
108-88-3	toluene	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
108-88-3	toluene	A4

· **MAK (German Maximum Workplace Concentration)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:** T Toxic

· **Hazard-determining components of labelling:**

dibutyl phthalate

xylene

· **Risk phrases:**

61 May cause harm to the unborn child.

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

38 Irritating to skin.

(Contd. on page 8)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

Trade name: AggreGloss™ J25

(Contd. of page 7)

· **Safety phrases:**

- 53 Avoid exposure - obtain special instructions before use.
- 2 Keep out of the reach of children.
- 9 Keep container in a well-ventilated place.
- 13 Keep away from food, drink and animal feedingstuffs.
- 16 Keep away from sources of ignition - No smoking.
- 20 When using do not eat or drink.
- 23 Do not breathe fumes/aerosol.
- 25 Avoid contact with eyes.
- 28 After contact with skin, wash immediately with plenty of soap and water.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 36/37/39 Wear suitable protective clothing, gloves and eyeface protection.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- 52 Not recommended for interior use on large surface areas.
- 64 If swallowed, rinse mouth with water (only if the person is conscious).

· **National regulations:**

- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information

The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing MSDS:** Environmental, Health & Safety Department
- **Contact:** Environmental, Health & Safety Manager

USA