

**OB - DEHYDRATINE #85 55 GL**

Version 2.0

Print Date 12/05/2013

REVISION DATE: 07/14/2012

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : OB - DEHYDRATINE #85 55 GL
Product code : THD5P55

COMPANY : Euclid Chemical Company
19218 Redwood Road
Cleveland, OH 44110

Telephone : 1-800-321-7628
Emergency Phone: : U.S. only: 1-800-424-9300
International Users Call Collect: 1-703-527-3887

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Brown. Liquid. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.
Eyes : Direct contact may cause mild irritation.
Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.
Skin : May cause mild irritation. May cause sensitization resulting in irritation, itching and redness. May cause a rash.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Prolonged or repeated skin contact with asphalt may result in skin sensitivity, such as irritation, rashes, and dermatitis. Prolonged or repeated exposure to polycyclic aromatic hydrocarbons and other volatiles which are contained in trace amounts in asphalt have been shown to cause cancer or respiratory damage in animals. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Eye, Lung

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Water	7732-18-5	40.0 - 70.0
Asphalt	8052-42-4	40.0 - 70.0
Inert Filler	NJ TSRN# 51721300-5013P	5.0 - 10.0
Potassium bi-chromate	7778-50-9	- <1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get

**OB - DEHYDRATINE #85 55 GL**

Version 2.0

Print Date 12/05/2013

REVISION DATE: 07/14/2012

	medical attention.
Eye contact	: Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
Skin contact	: Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	: Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point	: Not available.
Method	: Not available.
Lower explosion limit	: Not available.
Upper explosion limit	: Not available.
Autoignition temperature	: Not available.
Extinguishing media	: If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	: Carbon monoxide and carbon dioxide can form. Oxides of sulfur can form.
Protective equipment for firefighters	: Not applicable. Product is not expected to burn.
Fire and explosion conditions	: Not applicable, not expected to burn.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**Personal protection equipment**

Respiratory protection	: Not required under normal conditions of use.
Hand protection	: Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
Eye protection	: Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
Protective measures	: Use professional judgment in the selection, care, and use. Other equipment not normally required.
Engineering measures	: General ventilation is sufficient. Use local exhaust when the general

**OB - DEHYDRATINE #85 55 GL**

Version 2.0

Print Date 12/05/2013

REVISION DATE: 07/14/2012

ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Asphalt	8052-42-4	ACGIH TWA: benzene solubles	0.5 mg/m3	Inhalable fraction.as
Inert Filler	9004-34-6	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Total dust. Total dust. Respirable fraction.
Potassium bi-chromate	7778-50-9	ACGIH TWA: ACGIH TWA: OSHA PEL:	0.05 mg/m3 0.01 mg/m3 1 mg/m3	as Cr as Cr as Cr

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid
Color	: Brown
Odor	: Asphalt
pH	: 6 - 8
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: Not available.
Water solubility	: Dispersible
Specific Gravity	: 1.0
% Volatile Weight	: 49.1 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Oxidizing agents.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Potassium bi-chromate, CAS-No.: 7778-50-9	
Acute oral toxicity (LD-50 oral)	190 mg/kg (Mouse) 17 - 26 mg/kg (Rat)

**OB - DEHYDRATINE #85 55 GL**

Version 2.0

Print Date 12/05/2013

REVISION DATE: 07/14/2012

Acute inhalation toxicity (LC-50)	0.029 mg/l for 4 h (Fischer 344 rat) 0.035 mg/l for 4 h (Fischer 344 rat)
Acute dermal toxicity (LD-50 dermal)	403 - 490 mg/kg (New Zealand rabbit)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA**CFR / DOT:**

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION**North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : Potassium bi-chromate 7778-50-9

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

OSHA Hazardous Components :

Asphalt	8052-42-4
Inert Filler	NJ TSRN# 51721300-5013P
Potassium bi-chromate	7778-50-9

OSHA Status: Considered : Irritant
hazardous based on the Carcinogen
following criteria:



EUCLID CHEMICAL

OB - DEHYDRATINE #85 55 GL

Version 2.0

Print Date 12/05/2013

REVISION DATE: 07/14/2012

OSHA Flammability : Not Regulated

Regulatory VOC (less water and
exempt solvent) : 0 g/l

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Potassium bi-chromate 7778-50-9

U.S. State Regulations:

MASS RTK Components : Asphalt 8052-42-4
Inert Filler NJ TSRN# 51721300-5013P

Penn RTK Components : Water 7732-18-5
Asphalt 8052-42-4
Inert Filler NJ TSRN# 51721300-5013P

NJ RTK Components : Water 7732-18-5
Asphalt 8052-42-4
Inert Filler NJ TSRN# 51721300-5013P
Potassium bi-chromate 7778-50-9

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION**HMIS Rating :**

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum
1 = Slight
2 = Moderate
3 = Serious
4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol**Legend**

ACGIH - American Conference of Governmental Hygienists
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
DOT - Department of Transportation
DSL - Domestic Substance List
EPA - Environmental Protection Agency
HMIS - Hazardous Materials Information System
IARC - International Agency for Research on Cancer
MSHA - Mine Safety Health Administration
NDSL - Non-Domestic Substance List

PEL - Permissible Exposure Limit
RCRA - Resource Conservation and Recovery Act
RTK - Right To Know
SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TLV - Threshold Limit Value
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
V - Volume



EUCLID CHEMICAL

OB - DEHYDRATINE #85 55 GL

Version 2.0

Print Date 12/05/2013

REVISION DATE: 07/14/2012

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information System