

Version 2.0 **REVISION DATE: 07/08/2012** Print Date 12/21/2013

SECTION 1 - PRODUCT IDENTIFICATION

Trade name Product code

DURALTOP GEL A -

COMPANY

TA5103644 :

Euclid Chemical Company 19218 Redwood Road Cleveland, OH 44110 1-800-321-7628 Telephone Emergency Phone: U.S. only: 1-800-424-9300 : International Users Call Collect: 1-703-527-3887

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Gray. Powder. Dust may irritate nose and throat. Dust irritating to the respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation Eyes	: Dir	ist may irritate nose and throat. Dust irritating to the respiratory tract. rect contact may cause severe irritation. May cause mechanical irritation or abrasion, d possible chemical burns. May cause temporary injury.
Ingestion		ay cause irritation to the mouth, throat and stomach. May cause gastrointestinal tation, nausea, and vomiting.
Skin	Ma	ay cause severe irritation. May cause dryness, cracking, irritation, and chemical burns. ay produce cement dermatitis due to primary irritation from alkaline, hydroscopic and rasive properties.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %	
Portland cement	65997-15-1	30.0 - 60.0	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	30.0 - 60.0	
Amorphous silicon dioxide	NJ TSRN# 51721300-5881P	10.0 - 30.0	
Fly Ash	68131-74-8	5.0 - 10.0	
Calcium oxide	1305-78-8	3.0 - 7.0	
Amorphous silica	69012-64-2	1.0 - 5.0	
Amorphous silica	7631-86-9	1.0 - 5.0	
Aluminum oxide	1344-28-1	1.0 - 5.0	
An RPP Company	1/7		TA5103644



Version 2.0 REVISION DATE: 07/08/2012 Print Date 12/21/2013

Sulfur trioxide

7446-11-9

Center or Physician immediately.

1.0 - 5.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation: Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get
medical attention.Eye contact: Flush with water for at least 15 minutes while holding eye lids apart. Get medical
attention immediately.Skin contact: Clean area of contact thoroughly using soap and water. If irritation, rash or other
disorders develop, get medical attention immediately.Ingestion: Do not induce vomiting unless advised by a physician. Call nearest Poison Control

SECTION 5 - FIRE FIGHTING MEASURES

Flash point Method	:	Not available. Not available.
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	This product is not expected to burn under normal conditions of use.Use that which is appropriate to the surroundings.
Hazardous combustion products	:	Not available.
Protective equipment for firefighters	:	Not applicable. Product is not expected to burn.
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Dampen material with water to control dusting. Scoop up and transfer to appropriate container for disposal. Flush spill area with water.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of dust and contact with skin and eyes. Clean hands thoroughly after handling. Precautions also apply to emptied containers. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store in sealed containers in a cool, dry, ventilated warehouse location.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

An **RPM** Company



DOMALION OLLA		
Version 2.0 REVISION DATE: 07/08/2012		Print Date 12/21/2013
Respiratory protection	:	Wear appropriate, properly fitted NIOSH/MSHA approved dust respirator where airborne concentrations are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
Hand protection	:	Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
Eye protection	:	Wear appropriate eye protection.Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
Skin and body protection	:	Prevent contact with shoes and clothing.
Protective measures	:	Use professional judgment in the selection, care, and use.Wear gloves, head coverings and full body clothing as necessary to prevent skin irritation. Washable or disposable clothing may be used. Do not take unwashed clothing home. Work clothes should be washed separately from other clothing and the washing machine rinsed thoroughly following use. Inform the launderer of the proper procedures. Store work clothes and street clothes separately to prevent contamination.
Engineering measures	:	Use only in well ventilated areas. Provide maximum ventilation in enclosed areas.Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Portland cement	65997-15-1	OSHA PEL: OSHA PEL: ACGIH TWA:	5 mg/m3 15 mg/m3 1 mg/m3	Respirable fraction. Total dust. Respirable fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.
Calcium oxide	1305-78-8	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	2 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3	Total dust. Respirable fraction.
Amorphous silica	69012-64-2	OSHA PEL: OSHA PEL: OSHA TWA:	15 mg/m3 5 mg/m3 0.8 mg/m3	Total dust. Respirable fraction.
Amorphous silica	7631-86-9	ACGIH TWA: ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA:	3 mg/m3 10 mg/m3 15 mg/m3 5 mg/m3 0.8 mg/m3	Respirable particles. Inhalable particles. Total dust. Respirable fraction.



Print Date 12/21/2013

DURALTOP GEL A

Version 2.0 REVISION DATE: 07/08/2012

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Aluminum oxide	1344-28-1	ACGIH TWA:	10 mg/m3	
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	1 mg/m3	Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	:	Powder
Color	:	Gray
Odor	:	None
рН	:	Not available.
Vapour pressure	:	Not available.
Vapor density	:	Not available.
Melting point/range	:	Not available.
Freezing point	:	Not available.
Boiling point/range	:	Not available.
Water solubility	:	Miscible
Specific Gravity	:	3.5
% Volatile Weight	:	0.0 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Not Applicable.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Amorphous silica, CAS-No.: 7631-86-9 Acute oral toxicity (LD-50 oral)

22,500 mg/kg (Rat) 15,000 mg/kg (Mouse)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method

Method : Not regulated under RCRA. Dispose of in compliance with state and local regulations. Do not incinerate.



Version 2.0 **REVISION DATE: 07/08/2012** Print Date 12/21/2013

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory. This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

Crystalline Silica (Quartz)/ Silica		
Chemical is listed as an IARC, N	TP, OSHA, or ACGIH Carcinogen:	
VOC Method 310	: 0 %	
Regulatory VOC (less water and exempt solvent)	I : 0 g/I	
OSHA Flammability	: Not Regulated	
OSHA Status: Considered hazardous based on the following criteria:	: Irritant Carcinogen	
Aluminum oxide Sulfur trioxide	1344-28-1 7446-11-9	
Amorphous silica Amorphous silica	69012-64-2 7631-86-9	
Calcium oxide	1305-78-8	
OSHA Hazardous Components Portland cement Crystalline Silica (Quartz)/ Silica	65997-15-1	
SARA 311/312 Hazards	: Acute Health Hazard Chronic Health Hazard	
SARA 313 Components	: Aluminum oxide	1344-28-1



Print Date 12/21/2013

DURALTOP GEL A

Version 2.0 REVISION DATE: 07/08/2012

U.S. State Regulations: MASS RTK Components	: Portland cement 65997-15-1 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7 Calcium oxide 1305-78-8 Amorphous silica 69012-64-2 Amorphous silica 7631-86-9 Aluminum oxide 1344-28-1 Sulfur trioxide 7446-11-9
Penn RTK Components	 Portland cement Crystalline Silica (Quartz)/ Silica Sand Amorphous silicon dioxide Fly Ash Calcium oxide Amorphous silica Atuminum oxide Sulfur trioxide
NJ RTK Components	Portland cement65997-15-1Crystalline Silica (Quartz)/ Silica Sand14808-60-7Amorphous silicon dioxideNJ TSRN# 51721300-5881PFly Ash68131-74-8Calcium oxide1305-78-8Amorphous silica69012-64-2Sulfur trioxide7446-11-9

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	0
Reactivity	0
PPE	

0 = Minimum 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists	PEL - Permissible Exposure Limit
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act	RCRA - Resource Conservation and Recovery Act
DOT - Department of Transportation	RTK - Right To Know
DSL - Domestic Substance List	SARA - Superfund Amendments and Reauthorization Act

An **RPM** Company

Material Safety Data Sheet



DURALTOP GEL A

Version 2.0 REVISION DATE: 07/08/2012

EPA - Environmental Protection Agency HMIS - Hazardous Materials Information System IARC - International Agency for Research on Cancer MSHA - Mine Safety Health Administration NDSL - Non-Domestic Substance List NIOSH - National Institute for Occupational Safety and Health NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

Print Date 12/21/2013

STEL - Short Term Exposure Limit TLV - Threshold Limit Value TSCA - Toxic Substances Control Act TWA - Time Weighted Average V - Volume VOC - Volatile Organic Compound WHMIS - Workplace Hazardous Materials Information System