

Version 2.2

08/17/2006

1. PRODUCT AND COMPANY INFORMATION

Company	:	BASF Admixtures, Inc. 23700 Chagrin Blvd BEACHWOOD, OH 44122
Telephone	:	216-839-7500
Emergency telephone number	:	(800) 424-9300 (703) 527-3887 (Outside Continental US)
Product name	:	MBT EAC-S REGULAR & CLEAR
MSDS ID No.	:	10383
TSCA Inventory	:	All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.
Canadian DSL	:	All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List (DSL).

2. HAZARDOUS INGREDIENTS

Does not contain hazardous chemicals as defined by 29 CFR 1910.1200 and WHMIS.

3. HAZARDS IDENTIFICATION

HMIS [®] Rating		HEALTH 1	FLAMMABILITY 0	PHYSICAL HAZARD 0
WHMIS Class	:	D2B		
Primary Routes of Entry	:	Inhalation Eye contact Skin contact		
Effects of Overexposure				
Inhalation	:	Can cause slig	ght irritation.	
Skin	:	Can cause slig	ght irritation.	
Eyes	:	Can cause slig	ght irritation.	
Ingestion	:	Can cause slig	ght irritation.	
Chronic exposure	:	No known info	ormation available.	

4. FIRST AID MEASURES

Eye contact

: Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek



	medical attention.
Skin contact	: Remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.
Ingestion	: Do not induce vomiting without medical advice. If conscious, drink plenty of water. If a person feels unwell or symptoms of skin irritation appear, consult a physician. If a person vomits, place him/her in the recovery position. Never give anything by mouth to an unconscious person.
Inhalation	: Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immediate medical attention.

5. FIRE-FIGHTING MEASURES

Flash point	:	does not flash
Autoignition temperature	:	not applicable
Lower explosion limit	:	not applicable
Upper explosion limit	:	no data available
Suitable extinguishing media	:	Use extinguishing agent suitable for type of surrounding fire.
Fire and Explosion Hazards	:	Containers can build up pressure if exposed to heat (fire). Cool closed containers exposed to fire with water spray.
Special Fire-fighting Procedures	:	As in any fire, wear pressure demand self-contained breathing apparatus (NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Methods for cleaning up : Wear appropriate protective equipment (refer to section 8). Take action to eliminate source of leak; prevent from entry into open streams or sewers; contain spill by diking; vacuum up liquid or use absorbent media; remove to storage for disposal and rinse residual stain with water.

7. HANDLING AND STORAGE

Handling	:	Keep out of reach of children. For personal protection see section 8.
Storage	:	Keep tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye protection	:	Wear as appropriate: safety glasses with side-shields goggles face-shield
Hand protection	:	Wear as appropriate: impervious gloves



Body Protection	ear as appropriate: pervious clothing eventive skin protection	
Respiratory protection	case of insufficient ventilation wear suitable respiratory ecing concentrations above the exposure limit they must uspirators.	
Hygienic Practices	void contact with skin, eyes and clothing. Ensure adequa onfined areas. Wash hands before breaks and at the end ot eat, drink or smoke. Handle in accordance with good ir actice.	of workday. When using, do
Engineering Controls	ocal exhaust ventilation can be necessary to control any a _Vs during the use of this product.	air contaminants to within their

9. PHYSICAL AND CHEMICAL PROPERTIES

Color	:	various colors
Physical State	:	liquid
Odor	:	very faint
рН	:	6.0 - 6.5
Odor Threshold	:	no data available
Vapor Pressure	:	no data available
Vapor Density	:	no data available
Boiling point/range	:	212 °F (100 °C)
Freeze Point	:	32 °F (0 °C)
Water solubility	:	insoluble
Specific Gravity	:	0.99 - 1.11
Viscosity	:	no data available
Evaporation rate	:	no data available
Partition coefficient (n- octanol/water)	:	no data available
VOC Concentration as applied (less water and exempt solvents)	:	0 g/l

10. STABILITY AND REACTIVITY

Sta	bil	itv
ola		πιy

- : Stable under recommended storage conditions.
- Conditions to avoid : Prolonged exposure to high temperatures



Materials to avoid	:	None known.
Hazardous decomposition products	:	Oxides of carbon nitrogen oxides (NOx) hydrocarbons
Hazardous polymerization	:	Will not occur under normal conditions.

11. TOXICOLOGICAL INFORMATION

<u>Type</u> LC50	<u>Value</u> no data available	<u>Species</u>	Exposure time
<u>Type</u> LD50 (Oral)	<u>Value</u> no data available	<u>Species</u>	
<u>Type</u> LD50 (Dermal)	<u>Value</u> no data available	<u>Species</u>	
	LC50 <u>Type</u> LD50 (Oral) <u>Type</u>	LC50no data availableType LD50 (Oral)Value no data availableTypeValue	LC50no data availableType LD50 (Oral)Value no data availableSpeciesTypeValueSpecies

12. ECOLOGICAL INFORMATION

Ecotoxicological Information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.

14. TRANSPORT INFORMATION

DOT : Proper shipping name Not regulated

IATA : Proper shipping name Not regulated

15. REGULATORY INFORMATION

SARA 311/312 (RTK)

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to



meet the following categories:

not applicable

SARA 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

This product contains no chemicals subject to the SARA 313 supplier notification requirements.

CERCLA

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

RQ CAS No. Chemical Name

No CERCLA chemicals exist in this product above reportable concentrations.

TSCA Section 12(b) Export Notification

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

CAS No. Chemical Name

There are no TSCA 12(b) Chemicals in this product.

California Proposition 65

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

CAS No. Chemical Name

There are no Proposition 65 chemicals known to exist in this product.

16. OTHER INFORMATION

 Legend
 : N.E. - Not Established

 TLV - Threshold Limit Value

 STEL - Short Term Exposure Limit

 PEL - Permissible Exposure Limit

 CEIL - Ceiling

 Prepared By
 : Environment, Health and Safety Department

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be all inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

End of MSDS.