

EMACO T430

Version 1.2 11/24/2003

PRODUCT AND COMPANY INFORMATION

Company **Degussa Building Systems**

889 Valley Park Drive Shakopee, MN 55379

Telephone 952-496-6000

Emergency telephone number (800) 424-9300

(703) 527-3887 (Outside Continental US)

Product name EMACO T430

MSDS ID No. 10222

TSCA Inventory All components of this product are included, or are exempt from inclusion, in the EPA

Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Canadian DSL All components of this product are included, or are exempt from inclusion, in the

Canadian Domestic Substance List (DSL).

Product Use Description Mortar

2. HAZARDOUS INGREDIENTS

<u>Chemical</u>	CAS No.	<u>TLV</u>	<u>STEL</u>	<u>PEL</u>	<u>CEIL</u>	Weight %
SILICA, CRYSTALLINE QUARTZ	14808-60-7	0.05 mg/m3	N.E.	5 mg/m3	N.E.	40.00 - 70.00 %
FLY ASH	68131-74-8	N.E.	N.E.	N.E.	N.E.	15.00 - 40.00 %
PORTLAND CEMENT	65997-15-1	10 mg/m3	N.E.	5 mg/m3	N.E.	5.00 - 10.00 %
LIMESTONE	1317-65-3	5 mg/m3	N.E.	5 mg/m3	N.E.	1.00 - 5.00 %
SODIUM SULFATE	7757-82-6	N.E.	N.E.	N.E.	N.E.	1.00 - 5.00 %

3. HAZARDS IDENTIFICATION

PHYSICAL HMIS® Rating **HEALTH FLAMMABILITY HAZARD** 2

WHMIS Class D₂B

Ε

Primary Routes of Entry Ingestion

Inhalation Eye contact

Effects of Overexposure

Inhalation Inhalation of dust can cause coughing and labored breathing and possible temporary but

reversible irritation on mucous membranes and respiratory tract.

Skin Can cause slight to moderate irritation due to abrasive action. In combination with

water, repeated or prolonged dermal exposure can cause moderate to severe alkali

burns.

Eyes Can cause severe irritation, redness, tearing and blurred vision. Prolonged or repeated



EMACO T430

Version 1.2 11/24/2003

contact can cause burns and possibly corneal injury.

Ingestion Irritating to mouth, throat and stomach.

This product contains Crystalline (quartz) Silica which has been listed as a human Chronic exposure

carcinogen by NTP (Group 1) and IARC (Human Carcinogen) and a Suspected Human Carcinogen by ACGIH (catagory A2). Repeated or prolonged over exposure to free respirable Crystalline (quartz) silica can cause silicosis or other delayed and serious lung injury. Repeated or prolonged overexposure to free respirable silica can cause silicosis

or other delayed and serious lung injury.

Carcinogenicity

	ACGIH	IARC	NTP	OSHA
SILICA, CRYSTALLINE QUARTZ	Suspected human	Human carcinogen.	Known carcinogen.	N.E.
	carcinogen.			
FLY ASH	N.E.	N.E.	N.E.	N.E.
PORTLAND CEMENT	N.E.	N.E.	N.E.	N.E.
LIMESTONE	N.E.	N.E.	N.E.	N.E.
SODIUM SULFATE	NF	NF	NF	NF

4. FIRST AID MEASURES

Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek Eye contact

medical attention.

Skin contact Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of

water. Seek medical advice.

Ingestion Do not induce vomiting without medical advice. If conscious, drink plenty of water. Call a

physician immediately. Never give anything by mouth to an unconscious person. If a

person vomits, place him/her in the recovery position.

Inhalation Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing

has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immediate

medical attention.

5. FIRE-FIGHTING MEASURES

Flash point Not combustible.

Autoignition temperature Not combustible.

Lower explosion limit not applicable

Upper explosion limit not applicable

Suitable extinguishing media water fog

carbon dioxide (CO2)

dry chemical

alcohol-resistant foam

Fire and Explosion Hazards This product is alkaline and releases considerable heat on contact with small amounts of

water. Avoid contact between resulting hot alkaline paste and metallic aluminum. Such

contact could generate hydrogen gas.

Special Fire-fighting Procedures: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH

approved or equivalent) and full protective gear.



EMACO T430

Version 1.2 11/24/2003

6. ACCIDENTAL RELEASE MEASURES

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Clean thoroughly. After cleaning, flush away

traces with water. Keep in suitable, closed containers for disposal. Wear personal

protective equipment.

7. HANDLING AND STORAGE

Handling : Use only in area provided with appropriate ventilation. Keep out of reach of children.

Avoid exceeding of the given occupational exposure limits (see section 2). Avoid

formation of respirable particles.

Storage : Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye protection : Wear as appropriate:

safety glasses with side-shields

face-shield goggles

Hand protection : Wear as appropriate:

impervious gloves

Body Protection : Wear as appropriate:

preventive skin protection impervious clothing

Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment. When workers are

facing concentrations above the exposure limit they must use appropriate certified

respirators.

Hygienic Practices : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in

confined areas. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or

smoke.

Engineering Controls : Local exhaust ventilation can be necessary to control any air contaminants to within their

TLVs during the use of this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color : grey

Physical State : powder

Odor : none

pH (at 100 %) : not applicable

Odor Threshold : no data available

Vapor Pressure : not applicable



EMACO T430

Version 1.2 11/24/2003

Vapor Density : not applicable

Boiling point/range : no data available

Freeze Point : no data available

Water solubility : slightly soluble

Specific Gravity : no data available

Viscosity : no data available

Evaporation rate : no data available

Partition coefficient (n-

octanol/water)

no data available

VOC Concentration as applied

(less water and exempt

solvents)

0 g/l

10. STABILITY AND REACTIVITY

Stability : Stable under recommended storage conditions.

Conditions to avoid : no data available

Materials to avoid : strong acids and strong bases

strong oxidizing agents

Hazardous decomposition

Acute inhalation toxicity

products

no data available

Hazardous polymerization : Will not occur under normal conditions.

11. TOXICOLOGICAL INFORMATION

	<u>Type</u>	<u>Value</u>	Species	Exposure time
<u>Product</u>	LC50	no data available		

<u>Component</u>

SILICA, CRYSTALLINE QUARTZ

FLY ASH

PORTLAND CEMENT

LIMESTONE

SODIUM SULFATE

LC50

no data available

Acute oral toxicity

<u>Type</u> <u>Value</u> <u>Species</u> <u>Product</u> LD50 (Oral) no data available



EMACO T430

Version 1.2 11/24/2003

Component

LD50 (Oral)	1,300 mg/kg	
LD50 (Oral)	5,000 mg/kg	
LD50 (Oral)	2,000 mg/kg	
LD50 (Oral)	6,450 mg/kg	rat
LD50 (Oral)	5,989 mg/kg	mouse
	LD50 (Oral) LD50 (Oral) LD50 (Oral)	LD50 (Oral) 5,000 mg/kg LD50 (Oral) 2,000 mg/kg LD50 (Oral) 6,450 mg/kg

Acute dermal toxicity

Type	Value	Species

Product LD50 (Dermal) no data available

Component

SILICA, CRYSTALLINE QUARTZ	LD50 (Dermal)	no data available
FLY ASH	LD50 (Dermal)	no data available
PORTLAND CEMENT	LD50 (Dermal)	no data available
LIMESTONE	LD50 (Dermal)	no data available
SODIUM SULFATE	LD50 (Dermal)	no data available

12. ECOLOGICAL INFORMATION

Ecotoxicological Information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.

14. TRANSPORT INFORMATION

DOT : Proper shipping name Not regulated

IATA : Proper shipping name Not regulated

15. REGULATORY INFORMATION

SARA 311/312 (RTK)

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE (ACUTE) HEALTH HAZARD DELAYED (CHRONIC) HEALTH HAZARD

SARA 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:



EMACO T430

Version 1.2 11/24/2003

Weight % CAS No. Chemical Name

This product contains no chemicals subject to the SARA 313 supplier notification requirements.

CERCLA

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

RQ CAS No. Chemical Name

No CERCLA chemicals exist in this product above reportable concentrations.

TSCA Section 12(b) Export Notification

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

CAS No. Chemical Name

There are no TSCA 12(b) Chemicals in this product.

California Proposition 65

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

CAS No. Chemical Name

14808-60-7 SILICA, CRYSTALLINE QUARTZ

7440-38-2 ARSENIC

16. OTHER INFORMATION

Legend : N.E. - Not Established

TLV - Threshold Limit Value

STEL - Short Term Exposure Limit PEL - Permissible Exposure Limit

CEIL - Ceiling

Prepared By : Environment, Health and Safety Department

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be all inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

End of MSDS.