



EUCLID CHEMICAL

EUCOLASTIC/NEO SEAL PRIMERVersion 4.0
REVISION DATE: 10/08/2014

Print Date 10/09/2014

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : EUCOLASTIC/NEO SEAL PRIMER

Product code : 073R 94

COMPANY : Euclid Chemical Company
19218 Redwood Road
Cleveland, OH 44110

Telephone : 1-800-321-7628
Emergency Phone : U.S. only: 1-800-424-9300
International Users Call Collect: 1-703-527-3887

Product use : Primer

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Clear. Liquid. May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization.

Eyes : Vapor and/or mist may cause eye irritation.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause sensitization resulting in irritation, itching and redness.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. Prolonged or repeated exposure to xylene may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney damage. Xylene overexposure may affect fetal development. Prolonged or repeated contact/exposure to aromatic petroleum distillates may cause defatting, drying, and irritation of the skin, dermatitis, and central nervous system (CNS) effects. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. A long-term NTP study showed that oral exposure to toluene diisocyanate (TDI) caused cancer in rats and mice. A lifetime inhalation study sponsored by the International Isocyanate Institute did not show carcinogenic activity in rats. May cause allergic skin and

**EUCOLASTIC/NEO SEAL PRIMER**

Version 4.0

Print Date 10/09/2014

REVISION DATE: 10/08/2014

respiratory sensitization. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Eye, Lung, Liver, Kidney, Skin, Nerve

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Aromatic Polyisocyanate Resin	NJ TSRN# 51721300-5295P	40.0 - 70.0
Aromatic petroleum distillates	64742-95-6	15.0 - 40.0
1,2,4-Trimethylbenzene	95-63-6	15.0 - 40.0
Xylene	1330-20-7	7.0 - 13.0
1,3,5-Trimethylbenzene	108-67-8	3.0 - 7.0
Ethylbenzene	100-41-4	1.0 - 5.0
Cumene	98-82-8	0.1 - 1.0
2,4-Toluene diisocyanate	584-84-9	0.1 - 1.0
Toluene	108-88-3	0.1 - 1.0
4,4'-Methylene bis(phenylisocyanate)	101-68-8	0.1 - 1.0
Polymethylene polyphenyl isocyanate	9016-87-9	0.1 - 1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	: Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	: Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
Skin contact	: Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	: Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point	: 94 °F, 34 °C
Method	: Setaflash Closed Cup
Lower explosion limit	: Not available.
Upper explosion limit	: Not available.
Autoignition temperature	: Not available.
Extinguishing media	: If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	: Carbon monoxide and carbon dioxide can form. Smoke, fumes. Hydrocyanic acid and nitrogen oxides can form.



Version 4.0

Print Date 10/09/2014

REVISION DATE: 10/08/2014

- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : Product may ignite if heated in excess of its flash point. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors. Vapors may travel to sources of ignition and flashback.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not smoke, weld, generate sparks, or use flame near container. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Store under dry warehouse conditions away from heat and all ignition sources.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**Personal protection equipment**

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Select positive pressure supplied air respirator (TC19C or equivalent) for isocyanates.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
1,2,4-Trimethylbenzene	95-63-6	ACGIH TWA:	25 ppm	
Xylene	1330-20-7	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 150 ppm 435 mg/m3	

**EUCOLASTIC/NEO SEAL PRIMER**

Version 4.0

Print Date 10/09/2014

REVISION DATE: 10/08/2014

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
1,3,5-Trimethylbenzene	108-67-8	ACGIH TWA:	25 ppm	
Ethylbenzene	100-41-4	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 125 ppm 435 mg/m3	
Cumene	98-82-8	ACGIH TWA: OSHA PEL:	50 ppm 245 mg/m3	
2,4-Toluene diisocyanate	584-84-9	ACGIH TWA: ACGIH STEL:	0.005 ppm 0.02 ppm	
Toluene	108-88-3	ACGIH TWA: OSHA TWA:	20 ppm 200 ppm	
4,4'-Methylene bis(phenylisocyanate)	101-68-8	ACGIH TWA:	0.005 ppm	
Polymethylene polyphenyl isocyanate	9016-87-9	ACGIH TWA:	0.005 ppm	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid
Color	: Clear
Odor	: Solvent
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: > 250 °F, > 121 °C
Water solubility	: Negligible
Specific Gravity	: 0.96
% Volatile Weight	: 58.2 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Strong acids.Strong bases.Amines.Water or moisture.Alcohols.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur under normal conditions.

**EUCOLASTIC/NEO SEAL PRIMER**

Version 4.0
REVISION DATE: 10/08/2014

Print Date 10/09/2014

SECTION 11 - TOXICOLOGICAL INFORMATION

Xylene, CAS-No.: 1330-20-7	
Acute oral toxicity (LD-50 oral)	4,300 mg/kg (Rat) 1,590 mg/kg (Mouse) 6,670 mg/kg (Rat) 3,523 - 8,600 mg/kg (Rat) 5,627 mg/kg (Mouse)
Acute inhalation toxicity (LC-50)	6,350 mg/l for 4 h (Rat) 3,907 mg/l for 6 h (Mouse) 8,000 mg/l for 4 h (Rat)
Ethylbenzene, CAS-No.: 100-41-4	
Acute oral toxicity (LD-50 oral)	5,460 mg/kg (Rat) 3,500 mg/kg (Rat)
Acute dermal toxicity (LD-50 dermal)	17,800 mg/kg (Rabbit)
Cumene, CAS-No.: 98-82-8	
Acute oral toxicity (LD-50 oral)	2,910 mg/kg (Rat) 1,400 mg/kg (Rat)
Acute inhalation toxicity (LC-50)	2,000 mg/l for 7 h (Mouse) 8,000 mg/l for 4 h (Rat) 24.7 mg/l for 2 h (Mouse)
2,4-Toluene diisocyanate, CAS-No.: 584-84-9	
Acute oral toxicity (LD-50 oral)	5,800 mg/kg (Rat)
Acute inhalation toxicity (LC-50)	14 mg/l for 4 h (Rat) 10 mg/l for 4 h (Mouse) 13 mg/l for 4 h (Guinea pig) 11 mg/l for 4 h (Rabbit)
Toluene, CAS-No.: 108-88-3	
Acute oral toxicity (LD-50 oral)	2,600 - 7,500 mg/kg (Rat) 5,000 mg/kg (Rat)
Acute inhalation toxicity (LC-50)	26,700 mg/l for 1 h (Rat) 400 mg/l for 24 h (Mouse) 5,320 mg/l for 8 h (Mouse)
Acute dermal toxicity (LD-50 dermal)	12,124 mg/kg (Rabbit)
4,4'-Methylene bis(phenylisocyanate), CAS-No.: 101-68-8	
Acute inhalation toxicity (LC-50)	0.369 mg/l for 4 h (Rat) 0.38 mg/l for 4 h (Rat)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

RCRA Class : D001: Reportable Quantity = 100 lbs. (Characteristic of ignitability)
This classification applies only to the material as it was originally produced.

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

**EUCOLASTIC/NEO SEAL PRIMER**

Version 4.0

Print Date 10/09/2014

REVISION DATE: 10/08/2014

UN1133, Adhesives, 3, PG III

TDG:

UN1133, ADHESIVES, 3, PG III

IMDG:

UN1133, ADHESIVES, 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation.
Please refer to Bill of Lading.

SECTION 15 - REGULATORY INFORMATION**North American Inventories:**

All components are listed or exempt from the TSCA inventory.
One or more components are listed on the NDSL.

U.S. Federal Regulations:

SARA 313 Components	:	1,2,4-Trimethylbenzene	95-63-6
		Xylene	1330-20-7
		Ethylbenzene	100-41-4
		2,4-Toluene diisocyanate	584-84-9

SARA 311/312 Hazards	:	Acute Health Hazard
		Fire Hazard

OSHA Hazardous Components :

1,2,4-Trimethylbenzene	95-63-6
Xylene	1330-20-7
1,3,5-Trimethylbenzene	108-67-8
Ethylbenzene	100-41-4
Cumene	98-82-8
2,4-Toluene diisocyanate	584-84-9
Toluene	108-88-3
4,4'-Methylene bis(phenylisocyanate)	101-68-8
Polymethylene polyphenyl isocyanate	9016-87-9

OSHA Status: Considered	:	Irritant
hazardous based on the		Sensitizer
following criteria:		

OSHA Flammability	:	IC
-------------------	---	----

Regulatory VOC (less water and	:	559 g/l
exempt solvent)		
VOC Method 310	:	58.25 %

U.S. State Regulations:

MASS RTK Components	:	1,2,4-Trimethylbenzene	95-63-6
---------------------	---	------------------------	---------



EUCLID CHEMICAL

EUCOLASTIC/NEO SEAL PRIMER

Version 4.0

Print Date 10/09/2014

REVISION DATE: 10/08/2014

	Xylene	1330-20-7
	1,3,5-Trimethylbenzene	108-67-8
	Ethylbenzene	100-41-4
	2,4-Toluene diisocyanate	584-84-9
Penn RTK Components	: Aromatic Polyisocyanate Resin	NJ TSRN# 51721300-5295P
	Aromatic petroleum distillates	64742-95-6
	1,2,4-Trimethylbenzene	95-63-6
	Xylene	1330-20-7
	1,3,5-Trimethylbenzene	108-67-8
	Ethylbenzene	100-41-4
	2,4-Toluene diisocyanate	584-84-9
NJ RTK Components	: Aromatic Polyisocyanate Resin	NJ TSRN# 51721300-5295P
	Aromatic petroleum distillates	64742-95-6
	1,2,4-Trimethylbenzene	95-63-6
	Xylene	1330-20-7
	1,3,5-Trimethylbenzene	108-67-8
	Ethylbenzene	100-41-4
	Diethylbenzene, Mixed Isomers	25340-17-4

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION**HMIS Rating :**

Health	2
Flammability	3
Reactivity	2
PPE	

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol**Legend**

ACGIH - American Conference of Governmental Hygienists
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
 DOT - Department of Transportation
 DSL - Domestic Substance List
 EPA - Environmental Protection Agency
 HMIS - Hazardous Materials Information System
 IARC - International Agency for Research on Cancer
 MSHA - Mine Safety Health Administration

PEL - Permissible Exposure Limit
 RCRA - Resource Conservation and Recovery Act
 RTK - Right To Know
 SARA - Superfund Amendments and Reauthorization Act
 STEL - Short Term Exposure Limit
 TLV - Threshold Limit Value
 TSCA - Toxic Substances Control Act
 TWA - Time Weighted Average



EUCLID CHEMICAL

EUCOLASTIC/NEO SEAL PRIMER

Version 4.0

Print Date 10/09/2014

REVISION DATE: 10/08/2014

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information System