

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

1 Identification of substance

· Product details

· Trade name: Acrylic Bonding Agent J40

· Article number: 83-69081

· Application of the substance / the preparation

· Manufacturer/Supplier:

Dayton Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Composition/Data on components

· Chemical characterization:

· CAS No. Description

7732-18-5 water, distilled, conductivity or of similar purity

· Identification number(s) Not applicable

· EINECS Number: 231-791-2

· Chemical characterization

· Dangerous components:

7664-41-7	ammonia, anhydrous	≤ 1%
4719-04-4	2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol	≤ 1%

3 Hazards identification

· Hazard description: May cause eye and skin irritation. Prolonged contact may cause sensitization.

· Information pertaining to particular dangers for man and environment: Not applicable.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1

Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH	1
FIRE	0
PHYSICAL HAZARD	0

Health = 1

Fire = 0

Reactivity = 0

4 First aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 2)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

Trade name: Acrylic Bonding Agent J40

(Contd. of page 1)

- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Seek medical treatment.

5 Fire fighting measures

- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Protective equipment:**
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:** No special measures required.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Components with limit values that require monitoring at the workplace:**

7664-41-7 ammonia, anhydrous

PEL	35 mg/m ³ , 50 ppm
REL	Short-term value: 27 mg/m ³ , 35 ppm Long-term value: 18 mg/m ³ , 25 ppm
TLV	Short-term value: 24 mg/m ³ , 35 ppm Long-term value: 17 mg/m ³ , 25 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 3)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

Trade name: Acrylic Bonding Agent J40

(Contd. of page 2)

- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.
- **Breathing equipment:** Suitable respiratory protective device recommended.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· General Information

Form:	Liquid
Color:	Colorless
Odor:	Odorless

· Change in condition

Melting point/Melting range: 0°C (32°F)
Boiling point/Boiling range: 100°C (212°F)

· **Flash point:** Not applicable.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Vapor pressure at 20°C (68°F):** 23 hPa (17 mm Hg)

· **Density at 20°C (68°F):** 1 g/cm³

· Solubility in / Miscibility with

Water:	Not miscible or difficult to mix.
Organic solvents:	0.0 %
Water:	98.4 %

· **Solids content:** 25 %

· **Volatile Organic Compounds:** Contains less than 50 g/L.

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.

(Contd. on page 4)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

Trade name: Acrylic Bonding Agent J40

(Contd. of page 3)

· **Dangerous products of decomposition:** No dangerous decomposition products known.

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

7664-41-7 ammonia, anhydrous

Oral	LD50	350 mg/kg (rat)
Inhalative	LC50/4 h	2000 mg/l (rat)

· **Primary irritant effect:**

· **on the skin:** May cause skin irritation.

· **on the eye:** Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

12 Ecological information

· **General notes:**

Generally not hazardous for water

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Danger to drinking water if even extremely small quantities leak into the ground.

13 Disposal considerations

· **Product:**

· **Recommendation:**

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

· **DOT regulations:**

Not Regulated

· **Hazard class:**

N/A

· **Limited Quantity Exemption:**

No Limited Quantity exemption applies for this shipping class.

· **U.S. Domestic Ground Shipments:**

Same as listed for Standard Shipments above.

· **U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:**

Same as listed for Standard Shipments above.

· **Emergency Response Guide (ERG) Number:**

Not determine

· **Land transport ADR/RID (cross-border):**

Not Regulated

· **ADR/RID class:**

N/A

· **Maritime transport IMDG:**

Not Regulated

· **IMDG Class:**

N/A

(Contd. on page 5)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

Trade name: Acrylic Bonding Agent J40

(Contd. of page 4)

- | | |
|--|---------------|
| · Marine pollutant: | No |
| · Air transport ICAO-TI and IATA-DGR: | Not Regulated |
| · ICAO/IATA Class: | N/A |

15 Regulations

· Sara

· **Section 355 (extremely hazardous substances):**

7664-41-7 ammonia, anhydrous

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

7664-41-7 ammonia, anhydrous

≤1%

· **TSCA (Toxic Substances Control Act):**

Substance is listed.

· **Proposition 65**

· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for females:**

Substance is not listed.

· **Chemicals known to cause reproductive toxicity for males:**

Substance is not listed.

· **Chemicals known to cause developmental toxicity:**

Substance is not listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

Substance is not listed.

· **IARC (International Agency for Research on Cancer)**

7631-86-9 silicon dioxide, chemically prepared

3

· **NTP (National Toxicology Program)**

Substance is not listed.

· **TLV (Threshold Limit Value established by ACGIH)**

Substance is not listed.

· **MAK (German Maximum Workplace Concentration)**

Substance is not listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is not listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is not listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols: Xi Irritant**

(Contd. on page 6)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/27/2011

Reviewed on 09/27/2011

Trade name: Acrylic Bonding Agent J40

(Contd. of page 5)

· Hazard-determining components of labelling:

2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol
ammonia, anhydrous

· Risk phrases:

36/37/38 Irritating to eyes, respiratory system and skin.
43 May cause sensitisation by skin contact.

· Safety phrases:

13 Keep away from food, drink and animal feedingstuffs.
25 Avoid contact with eyes.
26 In case of contact with eyes, rinse immediately with plenty of
water and seek medical advice.
37 Wear suitable gloves.
46 If swallowed, seek medical advice immediately and show this
container or label.
64 If swallowed, rinse mouth with water (only if the person is
conscious).

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

USA