Printing date 10/18/2012

Reviewed on 10/18/2012

1 Identification of substance

- · Product details
- · Trade name: Pro-PoxyTM 204 Part A
- · Article number: 87-140112A
- Application of the substance / the preparation
- Manufacturer/Supplier: Unitex® 3101 Gardner Kansas city, MO 64120

Tel: (800) 821-5846 *Fax:* (816) 483-3149

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Composition/Data on components

- · Chemical characterization
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 75-100% 700)

• Additional information: For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- · Hazard description: May cause eye and skin irritation. Prolonged contact may cause sensitization.
- · Information pertaining to particular dangers for man and environment:

The product has to be labelled due to internationally acknowledged calculation procedures using the latest valid versions.

Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)

HEALTH	1	Health = 1
FIRE	1	Fire = 1
PHYSICAL HAZARD	0	Reactivity = 0

4 First aid measures

• *After inhalation:* Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 2)

USA

(Contd. of page 1)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 10/18/2012

Reviewed on 10/18/2012

Trade name: Pro-PoxyTM 204 - Part A

· After skin contact:

- Immediately wash with water and soap and rinse thoroughly.
- If skin irritation continues, consult a doctor.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Seek medical treatment.

5 Fire fighting measures

- Suitable extinguishing agents:
 - CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection:

Inform respective authorities in case of seepage into water course or sewage system.

- · Measures for cleaning/collecting:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

7 Handling and storage

- · Handling:
- · Information for safe handling:

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: No special measures required.
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool dry location.
- · Information about storage in one common storage facility: Store away from incompatible materials.
- Further information about storage conditions: Keep receptacle tightly sealed.

8 Exposure controls and personal protection

· Additional information about design of technical systems: No further data; see item 7.

• Components with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the creation were used as basis.
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- · Breathing equipment: Not required.

Printing date 10/18/2012

Reviewed on 10/18/2012

Trade name: Pro-PoxyTM 204 - Part A

· Protection of hands:

(Contd. of page 2)



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • Eye protection: Wear appropriate eye protection to prevent eye contact.

General Information	
Form:	Liquid
Color:	Grey
Odor:	Mild
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	$> 94^{\circ}C (> 201^{\circ}F)$
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Density at 20°C (68°F):	1.050 g/cm^3
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Solvent content:	
Organic solvents:	0.0 %
Solids content:	100.0 %
Volatile Organic Compounds:	Not determined

10 Stability and reactivity

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Dangerous reactions No dangerous reactions known.
- · Dangerous products of decomposition: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- \cdot on the skin: May cause skin irritation.
- on the eye: Irritating effect.
- \cdot Sensitization: Sensitization possible through skin contact.
- \cdot Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 4)

Printing date 10/18/2012

Reviewed on 10/18/2012

Trade name: Pro-PoxyTM 204 - Part A

Irritant

(Contd. of page 3)

12 Ecological information

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

13 Disposal considerations

- · Product:
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to Federal, State, and Local regulations.

DOT regulations:	Not Regulated
Hazard class:	N/A
Packing group:	III
Remarks:	Add "Marine Pollutant" to end of proper shipping name if shipping is a bulk container (>119 gallons).
Limited Quantity Exemption:	No Limited Quantity exemption applies for this shipping class.
U.S. Domestic Ground Shipments:	Same as listed for Standard Shipments above.
· U.S. Domestic Ground Non-Bulk (119 gal or less	per
container) Shipments:	Same as listed for Standard Shipments above.
Emergency Response Guide (ERG) Number:	Not determine
Land transport ADR/RID (cross-border):	
ADR/RID class:	N/A
UN-Number:	
Packaging group:	III
• Maritime transport IMDG:	
· IMDG Class:	9
· UN Number:	3082
Packaging group:	III
Marine pollutant:	Yes
Propper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S (epoxy resin)

(Contd. of page 4)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 10/18/2012

Reviewed on 10/18/2012

Trade name: Pro-PoxyTM 204 - Part A

· Air transport ICAO-TI and IATA-DGR:

• Packaging group:

III

15 Regulations

· Sara

• Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

 \cdot Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

 \cdot IARC (International Agency for Research on Cancer)

13463-67-7 titanium dioxide

· NTP (National Toxicology Program)

None of the ingredients is listed.

• TLV (Threshold Limit Value established by ACGIH)

13463-67-7 titanium dioxide

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 titanium dioxide

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:

Xi Irritant

N Dangerous for the environment

USA

3

A4

USA

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 10/18/2012

Reviewed on 10/18/2012

Trade name: Pro-PoxyTM 204 - Part A

	(Contd. of page 5)
• <i>Hazard-determining components of labelling:</i> reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number averagemolecular weight = 700)	
 <i>Risk phrases:</i> 36/38 Irritating to eyes and skin. 43 May cause sensitisation by skin contact. 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. 	
 Safety phrases: Keep out of the reach of children. 24/25 Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of (to be specified by the manufacturer). 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. 37/39 Wear suitable gloves and eye/face protection. If swallowed, seek medical advice immediately and show this container or label. Use appropriate container to avoid environmental contamination. This material and its container must be disposed of as hazardous waste. If swallowed, rinse mouth with water (only if the person is conscious). 	
• Special labeling of certain preparations: Contains epoxy constituents. See information supplied by the manufacturer.	
· National regulations:	
• Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Environmental, Health & Safety Department

· Contact: Environmental, Health & Safety Manager

Printing date 10/19/2012

Reviewed on 10/19/2012

1 Identification of substance

- · Product details
- · Trade name: Pro-PoxyTM 204 Part B
- · Article number: 87-140112B
- \cdot Application of the substance / the preparation
- Manufacturer/Supplier: Unitex® 3101 Gardner Kansas city, MO 64120

Tel: (800) 821-5846 *Fax:* (816) 483-3149

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Composition/Data on components

- · Chemical characterization
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
694-83-7	cyclohex-1,2-ylenediamine	25-50%
84852-15-3	4-nonylphenol, branched	25-50%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	<i>≤</i> 5%
· Additional i	<i>information:</i> For the wording of the listed risk phrases refer to section 16.	

3 Hazards identification

· Hazard description: Not applicable.

- · Information pertaining to particular dangers for man and environment:
- The product has to be labelled due to internationally acknowledged calculation procedures using the latest valid versions.
- Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

 \cdot NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)

HEALTH	3	Health = 3
FIRE	1	Fire = 1
PHYSICAL HAZARD	2	Reactivity = 2

4 First aid measures

• General information:

Immediately remove any clothing soiled by the product.

(Contd. on page 2)

USA

(Contd. of page 1)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 10/19/2012

Reviewed on 10/19/2012

Trade name: Pro-PoxyTM 204 - Part B

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Seek medical treatment.

5 Fire fighting measures

 \cdot Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

· Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.

Measures for environmental protection: Inform respective authorities in case of seepage into water course or sewage system.
Measures for cleaning/collecting: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

7 Handling and storage

- · Handling:
- Information for safe handling:

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: No special measures required.
- · Storage:

• Requirements to be met by storerooms and receptacles: Store in a cool dry location.

- · Information about storage in one common storage facility: Store away from incompatible materials.
- Further information about storage conditions: Keep receptacle tightly sealed.

8 Exposure controls and personal protection

• Additional information about design of technical systems: No further data; see item 7.

• Components with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Printing date 10/19/2012

Reviewed on 10/19/2012

Trade name: Pro-PoxyTM 204 - Part B

	(Contd. of page 2)
Additional information: The lists that were valid during the creation were used as basis.	
Personal protective equipment:	
General protective and hygienic measures:	
Keep away from foodstuffs, beverages and feed.	
Immediately remove all soiled and contaminated clothing.	
Wash hands before breaks and at the end of work.	
Avoid contact with the eyes and skin.	
Breathing equipment: Not required.	
Protection of hands:	
Protective gloves	

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • Eye protection: Wear appropriate eye protection to prevent eye contact.

General Information	
Form:	Liquid
Color:	Grey
Odor:	Distinctive
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	$> 94^{\circ}C (> 201^{\circ}F)$
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Density at $20^{\circ}C$ (68°F):	0.960 g/cm ³
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Solvent content:	
Organic solvents:	0.0 %
Solids content:	100 %
Volatile Organic Compounds:	Not determined

10 Stability and reactivity

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Dangerous reactions No dangerous reactions known.
- · Dangerous products of decomposition: No dangerous decomposition products known.

(Contd. on page 4)

USA

(Contd. of page 3)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 10/19/2012

Reviewed on 10/19/2012

Trade name: Pro-PoxyTM 204 - Part B

11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

- Corrosive
- Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

12 Ecological information

- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water Must not reach bodies of water or drainage ditch undiluted or unneutralized. Also poisonous for fish and plankton in water bodies. Very toxic for aquatic organisms

13 Disposal considerations

- · Product:
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to Federal, State, and Local regulations.

14 Transport information	
· DOT regulations:	regulations: rd class: 8 ification number: UN1760 ing group: III rr shipping name (technical name): CORROSIVE LIQUID, N.O.S. (nonylphenol) 8
AL 21 COTREME S	
· Hazard class:	8
· Identification number:	UN1760
· Packing group:	III
· Proper shipping name (technical name):	CORROSIVE LIQUID, N.O.S. (nonylphenol)
·Label	8
· Remarks:	
· Limited Quantity Exemption:	Limited Quantity applies for inner packages 1 gallon or smaller.
	(Contd. on page 5)

Printing date 10/19/2012

Reviewed on 10/19/2012

Trade name: Pro-PoxyTM 204 - Part B

	(Contd. of pag
· U.S. Domestic Ground Shipments:	Same as listed for Standard Shipments above.
· U.S. Domestic Ground Non-Bulk (119 gal or less	
container) Shipments:	Same as listed for Standard Shipments above.
· Emergency Response Guide (ERG) Number:	Not determine
• Land transport ADR/RID (cross-border):	
· ADR/RID class:	8 Corrosive substances
· UN-Number:	1760
· Packaging group:	III
· Description of goods:	1760 CORROSIVE LIQUID, N.O.S. (nonylphenol)
· IMDG Class:	8
· UN Number:	1760
· Label	8
· Packaging group:	III
• Marine pollutant:	Yes
Propper shipping name:	CORROSIVE LIQUID, N.O.S. (nonylphenol)
• Air transport ICAO-TI and IATA-DGR:	
· ICAO/IATA Class:	8
· UN/ID Number:	1760
· Label	8
· Packaging group:	III
· Propper shipping name:	CORROSIVE LIQUID, N.O.S. (nonylphenol)

15 Regulations

· Sara
· Section 355 (extremely hazardous substances):
None of the ingredient is listed.
· Section 313 (Specific toxic chemical listings):
This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.
None of the ingredients is listed.
· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 6)

Printing date 10/19/2012

Reviewed on 10/19/2012

Trade name: Pro-PoxyTM 204 - Part B

Propos	ition 65 (Contd. of pag
Chemi	cals known to the State of California (Prop. 65) to cause cancer:
None o	f the ingredients is listed.
Chemi	cals known to cause reproductive toxicity for females:
None o	f the ingredients is listed.
Chemi	cals known to cause reproductive toxicity for males:
None o	f the ingredients is listed.
Chemi	cals known to cause developmental toxicity:
None o	f the ingredients is listed.
Cancer	rogenity categories
EPA (I	Environmental Protection Agency)
None o	f the ingredients is listed.
IARC ((International Agency for Research on Cancer)
None o	f the ingredients is listed.
NTP (I	National Toxicology Program)
None o	f the ingredients is listed.
TLV (1	Threshold Limit Value established by ACGIH)
None o	f the ingredients is listed.
MAK (German Maximum Workplace Concentration)
None o	f the ingredients is listed.
NIOSE	I-Ca (National Institute for Occupational Safety and Health)
None o	f the ingredients is listed.
OSHA-	Ca (Occupational Safety & Health Administration)
None o	f the ingredients is listed.
The pro Hazara C Corr	e t related hazard informations: oduct has been classified and marked in accordance with directives on hazardous materials. I symbols: gerous for the environment
cyclohe	l-determining components of labelling: ex-1,2-ylenediamine lphenol, branched
34 43 62 50/53	hrases: Harmful if swallowed. Causes burns. May cause sensitisation by skin contact. Possible risk of impaired fertility. Very toxic to aquatic organisms, may cause long-term adverse ffects in the aquatic environment.

63 Possible risk of harm to the unborn child.

(Contd. on page 7)

Printing date 10/19/2012

Reviewed on 10/19/2012

Trade name: Pro-PoxyTM 204 - Part B

· Safety phrases:

- 2 Keep out of the reach of children.
- 13 Keep away from food, drink and animal feedingstuffs.
- 20 When using do not eat or drink.
- 25 Avoid contact with eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 27/28 After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- 52 Not recommended for interior use on large surface areas.
- 57 Use appropriate container to avoid environmental contamination.
- 60 This material and its container must be disposed of as hazardous waste.
- 64 If swallowed, rinse mouth with water (only if the person is conscious).

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Environmental, Health & Safety Department

· Contact: Environmental, Health & Safety Manager

USA