

Version 2.0 Print Date 01/27/2015

REVISION DATE: 07/08/2012

### **SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : HEY'DI RAPID POWDER - BULK

Product code : R21247

COMPANY : Euclid Chemical Company

19218 Redwood Road Cleveland, OH 44110

Telephone : 1-800-321-7628

Emergency Phone: U.S. only: 1-800-424-9300

International Users Call Collect: 1-703-527-3887

#### **SECTION 2 - HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Dark Gray. Powder. Dust may irritate nose and throat. Dust irritating to the respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

### **Acute Potential Health Effects/ Routes of Entry**

Inhalation : Dust may irritate nose and throat. Dust irritating to the respiratory tract.

Eyes : Direct contact may cause severe irritation. May cause mechanical irritation or abrasion,

and possible chemical burns. May cause temporary injury.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal

irritation, nausea, and vomiting.

Skin : May cause severe irritation. May cause dryness, cracking, irritation, and chemical burns.

May produce cement dermatitis due to primary irritation from alkaline, hydroscopic and

abrasive properties.

#### **Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

#### **Chronic Health Effects**

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica.

# **SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Portland cement	65997-15-1	40.0 - 70.0
Fused calcium aluminate	NJ TSRN# 51721300-5813P	30.0 - 60.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	15.0 - 40.0
Calcium oxide	1305-78-8	1.0 - 5.0



Version 2.0 Print Date 01/27/2015

REVISION DATE: 07/08/2012

### **SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get

medical attention.

Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical

attention immediately.

Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other

disorders develop, get medical attention immediately.

Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control

Center or Physician immediately.

### **SECTION 5 - FIRE FIGHTING MEASURES**

Flash point : Not available.

Method : Not available.

Lower explosion limit : Not available.

Upper explosion limit : Not available.

Autoignition temperature : Not available.

Extinguishing media : This product is not expected to burn under normal conditions of use. Use

that which is appropriate to the surroundings.

Hazardous combustion

products

Not available.

Protective equipment for

firefighters

Not applicable. Product is not expected to burn.

Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

### **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Dampen material with water to control dusting. Scoop up and transfer to appropriate container for disposal. Flush spill area with water.

#### **SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of dust and contact with skin and eyes. Clean hands thoroughly after handling. Precautions also apply to emptied containers. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store in sealed containers in a cool, dry, ventilated warehouse location.

### **SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### Personal protection equipment



Version 2.0 Print Date 01/27/2015

**REVISION DATE: 07/08/2012** 

Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved dust respirator

where airborne concentrations are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.

Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to

reduce exposure.

Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face

shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily

available.

Skin and body protection : Prevent contact with shoes and clothing.

Protective measures : Use professional judgment in the selection, care, and use. Wear gloves, head

coverings and full body clothing as necessary to prevent skin irritation. Washable or disposable clothing may be used. Do not take unwashed clothing home. Work clothes should be washed separately from other clothing and the washing machine rinsed thoroughly following use. Inform the launderer of the proper procedures. Store work clothes and street clothes

separately to prevent contamination.

Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed

areas. Use local exhaust when the general ventilation is inadequate.

#### **Exposure Limits**

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Portland cement	65997-15-1	OSHA PEL: OSHA PEL: ACGIH TWA:	5 mg/m3 15 mg/m3 1 mg/m3	Respirable fraction. Total dust. Respirable fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.
Calcium oxide	1305-78-8	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	2 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3	Total dust. Respirable fraction.

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form : Powder
Color : Dark Gray
Odor : None

pH : Not available.

Vapour pressure : Not available.

Vapor density : Not available.

Melting point/range : Not available.

# Material Safety Data Sheet



# HEY'DI RAPID POWDER - BULK

Version 2.0 Print Date 01/27/2015

**REVISION DATE: 07/08/2012** 

Freezing point : Not available.

Boiling point/range : Not available.

Water solubility : Miscible

Specific Gravity : 3.1

% Volatile Weight : 0.0 %

### **SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Not Applicable.

Stability : Material is stable under normal storage, handling, and use.

Hazardous polymerization : Will not occur under normal conditions.

# **SECTION 11 - TOXICOLOGICAL INFORMATION**

No Data Available

### **SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

### **SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Not regulated under RCRA. Dispose of in compliance with state and local regulations.

Do not incinerate.

# **SECTION 14 - TRANSPORTATION / SHIPPING DATA**

### CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

### **SECTION 15 - REGULATORY INFORMATION**

#### **North American Inventories:**

All components are listed or exempt from the TSCA inventory.

An RPM Company



Version 2.0 Print Date 01/27/2015

REVISION DATE: 07/08/2012

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

OSHA Hazardous Components:

Portland cement 65997-15-1 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7 Calcium oxide 1305-78-8

OSHA Status: Considered : Irritant hazardous based on the Carcinogen

following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 0 g/l

exempt solvent)

VOC Method 310 : 0%

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen: Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

U.S. State Regulations:

MASS RTK Components : Portland cement 65997-15-1

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7 Calcium oxide 1305-78-8

Penn RTK Components Portland cement 65997-15-1

> Fused calcium aluminate NJ TSRN# 51721300-5813P

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7 Calcium oxide 1305-78-8

NJ RTK Components Portland cement 65997-15-1

> Fused calcium aluminate NJ TSRN# 51721300-5813P

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Calcium oxide 1305-78-8

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm



Version 2.0 Print Date 01/27/2015

REVISION DATE: 07/08/2012

### **SECTION 16 - OTHER INFORMATION**

### **HMIS Rating:**

Health	2	0 = Minimum
Flammability	0	1 = Slight
Reactivity	0	2 = Moderate
PPE		3 = Serious
		4 = Severe

#### Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

### Prepared by: Rich Mikol

#### Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System