



SECTION I: PRODUCT INFORMATION

PRODUCT: **Sikaflex® 1A (all colors) (MSDS# 4016)**REVISION DATE: February 1st, 2012

USAGE: ONE COMPONENT URETHANE BASED SEALANT

MANUFACTURER/SUPPLIER: SIKA CANADA INC.
 601, avenue Delmar
 Pointe Claire, QC
 H9R 4A9

EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666

TDG CLASSIFICATION: Not Regulated
 UN NUMBER: Not Established
 Packaging Group: Not Applicable

WHMIS Classification: B3, D2A
 Class: Not Applicable

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (mg/kg) (species, route)	LC ₅₀ (species, route)
CALCIUM OXIDE	1-5	Not Available	1305-78-8	Not Available	Not Available
XYLENE	1-5	ACGIH 100ppm (TWA) 150ppm (STEL)	1330-20-7	4300 (rat, oral)	6350ppm/4H
POLYOL AND ISOCYANATE PREPOLYMER	15-40	Not Established	Not Available	Not Established	Not Established

SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Paste
 Appearance and Odor: Aromatic odor with various colors
 Odor Threshold: Not Established
 Evaporation Rate: Not Established
 Vapor Density: Not Established
 Vapor Pressure: Not Established

Boiling Point: Not Established
 Freezing Point: Not Established
 Density: 1.2 g/ml
 Water Solubility: Not Established
 pH: Not Established
 % volatile: < 4%
 Water/Oil Distribution: Not Established

PRODUCT: **Sikaflex® 1A (all colors)**

MSDS# 4016

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability:	Combustible	TDG inflammability Class:	Not Regulated
If Yes, under what conditions:	Flame, spark	Flammable upper limits (% vol.):	Not Established
		Flammable lower limits (% vol.):	Not Established
		Flash Point (method used):	> 80°C (TCC)
Extinguishing methods:	Foam, dry chemical products, CO ₂ , water for large flames.	Auto-ignition temperature:	Not Established
		Dangerous Combustion Products:	Carbon oxides, Aldehydes, Ketones, HCL, Nitrogen oxide, MDI, TDI
Special Methods:	Firefighters must wear complete protective clothing with respiratory equipment and they must protect any exposed skin. Heated isocyanates react strongly with water.	Protect from mechanical impact:	No
		Protect from static discharge:	No

SECTION V: REACTIVITY DATA

Chemical stability:	Yes	Dangerous decomposition products:	Carbon oxides, Aldehydes, Ketones, HCL, Nitrogen oxide, MDI, TDI
If not, under what conditions			
Incompatibility with other material:	Yes	Polymerization Risks:	No
If Yes, which ones:	Acid, strong oxidizer, amine.		

PRODUCT: **Sikaflex® 1A (all colors)**

MSDS# 4016

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: Irritating

Carcinogenicity: Not Established

Skin: Irritating. Contact may result in dermatitis, allergic reactions, and sensitization.

Toxic effects on reproduction: Not Established

Inhalation: Vapor or mist from this product may cause irritation.

Teratogenicity: Xylene is classified as a development toxicant (Embryo toxin)

Ingestion: May cause nausea, vomiting, diarrhea, gastro-intestinal system disorder, constipation.

Mutagenicity: Not Established

Over exposure may cause breathing difficulties, sensitization, headaches, nausea, vomiting. May aggravate respiratory, skin, eye, lung problems and allergies.

If the product is applied according to the manufacturer, none of these symptoms should be encountered.

A person who is sensitized to isocyanate may have a reaction with a level of isocyanate well below the T.L.V.

Xylene is a central nervous system depressor and in rare cases, may cause a sensitization of the heart muscle causing arrhythmia.

Product with synergistic effects: Not Established

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems. An over exposure may cause death.

PRODUCT: **Sikaflex® 1A (all colors)****MSDS# 4016****SECTION VII: PREVENTIVE MEASURES****PERSONAL PROTECTIVE EQUIPMENT**

Gloves: Use chemical resistant gloves.

Respiratory equipment: Not necessary under normal use.

Eyes: Full-face mask or safety glasses

Shoes: Ordinary

Clothing: Rubber Apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required.

Procedure in case of leaks: Absorb with sand or other absorbent material.

Handling and Equipment methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, dry and well ventilated area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: Sikaflex® 1A (all colors)

MSDS# 4016

SECTION VIII: FIRST AID

Skin: Remove contaminated clothing and shoes.
Wash immediately with plenty of water.
Wash clothing before re-wearing.
Consult a physician if required.

Eyes: Rinse eyes immediately with plenty of water for several minutes, while holding eyelids wide open, to ensure a proper wash.
See a physician immediately.

Inhalation: In the case of overexposure, evacuate to fresh air.
Consult a physician if required.

Ingestion: Drink plenty of water. Do not induce vomiting.
Do not give anything by mouth to an unconscious person.
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared By: The Laboratory, Research and Development Department of Sika Canada Inc.
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.