

**CEMENT WASH**

Version 3.0  
REVISION DATE: 11/18/2014

Print Date 11/20/2014

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : CEMENT WASH

Product code : TR5114750

COMPANY : Euclid Chemical Company  
19218 Redwood Road  
Cleveland, OH 44110

Telephone : 1-800-321-7628

Emergency Phone : U.S. only: 1-800-424-9300  
International Users Call Collect: 1-703-527-3887

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Gray. Powder. Dust may irritate nose and throat. Dust irritating to the respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : Dust may irritate nose and throat. Dust irritating to the respiratory tract.

Eyes : Direct contact may cause severe irritation. May cause mechanical irritation or abrasion, and possible chemical burns. May cause temporary injury.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause severe irritation. May cause dryness, cracking, irritation, and chemical burns. May produce cement dermatitis due to primary irritation from alkaline, hygroscopic and abrasive properties.

**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica.

**SECTION 3 - PRODUCT COMPOSITION**

| Chemical Name                            | CAS-No.                 | Weight %    |
|--|-------------------------|-------------|
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7              | 40.0 - 70.0 |
| Portland cement                          | 65997-15-1              | 40.0 - 70.0 |
| Vinyl acetate copolymer                  | NJ TSRN# 51721300-5890P | 1.0 - 5.0   |
| Aluminum oxide                           | 1344-28-1               | 0.1 - 1.0   |

**CEMENT WASH**

Version 3.0  
REVISION DATE: 11/18/2014

Print Date 11/20/2014

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- |              |   |   |
|--------------|---|---|
| Inhalation   | : | Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.                                  |
| Eye contact  | : | Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.                                 |
| Skin contact | : | Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately. |
| Ingestion    | : | Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.                        |

**SECTION 5 - FIRE FIGHTING MEASURES**

- |                                       |   |   |
|---------------------------------------|---|---|
| Flash point                           | : | Not available.  |
| Method                                | : | Not applicable.   |
| Lower explosion limit                 | : | Not available.  |
| Upper explosion limit                 | : | Not available.  |
| Autoignition temperature              | : | Not available.  |
| Extinguishing media                   | : | This product is not expected to burn under normal conditions of use. Use that which is appropriate to the surroundings. |
| Hazardous combustion products         | : | Not available.  |
| Protective equipment for firefighters | : | Not applicable. Product is not expected to burn.  |
| Fire and explosion conditions         | : | This product not expected to ignite under normal conditions of use.   |

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Dampen material with water to control dusting. Scoop up and transfer to appropriate container for disposal. Flush spill area with water.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of dust and contact with skin and eyes. Clean hands thoroughly after handling. Precautions also apply to emptied containers. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store in sealed containers in a cool, dry, ventilated warehouse location.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

**CEMENT WASH**

Version 3.0

Print Date 11/20/2014

REVISION DATE: 11/18/2014

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved dust respirator where airborne concentrations are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use. Wear gloves, head coverings and full body clothing as necessary to prevent skin irritation. Washable or disposable clothing may be used. Do not take unwashed clothing home. Work clothes should be washed separately from other clothing and the washing machine rinsed thoroughly following use. Inform the launderer of the proper procedures. Store work clothes and street clothes separately to prevent contamination.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

| <b>Chemical Name</b>                        | <b>CAS Number</b> | <b>Regulation</b> | <b>Limit</b>            | <b>Form</b>   |
|---|-------------------|-------------------|-------------------------|---|
| Crystalline Silica (Quartz)/<br>Silica Sand | 14808-60-7        | OSHA TWA:         | 0.1 mg/m <sup>3</sup>   | Respirable.   |
|   |                   | OSHA TWA:         | 0.3 mg/m <sup>3</sup>   | Total dust.   |
|   |                   | ACGIH TWA:        | 0.025 mg/m <sup>3</sup> | Respirable fraction.  |
| Portland cement                             | 65997-15-1        | ACGIH TWA:        | 1 mg/m <sup>3</sup>     | Respirable fraction.  |
| Aluminum oxide                              | 1344-28-1         | ACGIH TWA:        | 10 mg/m <sup>3</sup>    | Total dust.<br>Respirable fraction.<br>Respirable fraction. |
|   |                   | OSHA TWA:         | 15 mg/m <sup>3</sup>    |   |
|   |                   | OSHA TWA:         | 5 mg/m <sup>3</sup>     |   |
|   |                   | ACGIH TWA:        | 1 mg/m <sup>3</sup>     |   |

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Powder
- Color : Gray
- Odor : None
- pH : 12
- Vapour pressure : Not available.
- Vapor density : Not available.
- Melting point/range : Not available.
- Freezing point : Not available.

**CEMENT WASH**

Version 3.0  
REVISION DATE: 11/18/2014

Print Date 11/20/2014

Boiling point/range : Not available.  
Water solubility : Miscible  
Specific Gravity : 3.5  
% Volatile Weight : 0.0 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Not Applicable.  
Stability : Material is stable under normal storage, handling, and use.  
Hazardous polymerization : Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

No Data Available

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Not regulated under RCRA. Dispose of in compliance with state and local regulations.  
Do not incinerate.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA****CFR / DOT:**

Not Regulated

**TDG:**

Not Regulated

**IMDG:**

Not Regulated

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**  
All components are listed or exempt from the TSCA inventory.

**CEMENT WASH**

Version 3.0

Print Date 11/20/2014

REVISION DATE: 11/18/2014

One or more components are listed on the NDSL.

**U.S. Federal Regulations:**

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard  
Chronic Health Hazard

## OSHA Hazardous Components :

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7  
Portland cement 65997-15-1  
Aluminum oxide 1344-28-1OSHA Status: Considered : Irritant  
hazardous based on the Carcinogen  
following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 0 g/l  
exempt solvent)

VOC Method 310 : 0.00 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

**U.S. State Regulations:**MASS RTK Components : Crystalline Silica (Quartz)/ Silica Sand 14808-60-7  
Portland cement 65997-15-1Penn RTK Components : Crystalline Silica (Quartz)/ Silica Sand 14808-60-7  
Portland cement 65997-15-1NJ RTK Components : Crystalline Silica (Quartz)/ Silica Sand 14808-60-7  
Portland cement 65997-15-1  
Vinyl acetate copolymer NJ TSRN# 51721300-5890P

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

**SECTION 16 - OTHER INFORMATION****HMIS Rating :**

|              |   |
|--------------|---|
| Health       | 2 |
| Flammability | 0 |
| Reactivity   | 0 |
| PPE          |   |

0 = Minimum  
1 = Slight  
2 = Moderate  
3 = Serious  
4 = Severe



## CEMENT WASH

Version 3.0

Print Date 11/20/2014

REVISION DATE: 11/18/2014

### Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

### Legend

ACGIH - American Conference of Governmental Hygienists  
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
DOT - Department of Transportation  
DSL - Domestic Substance List  
EPA - Environmental Protection Agency  
HMIS - Hazardous Materials Information System  
IARC - International Agency for Research on Cancer  
MSHA - Mine Safety Health Administration  
NDSL - Non-Domestic Substance List  
NIOSH - National Institute for Occupational Safety and Health  
NTP - National Toxicology Program  
OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit  
RCRA - Resource Conservation and Recovery Act  
RTK - Right To Know  
SARA - Superfund Amendments and Reauthorization Act  
STEL - Short Term Exposure Limit  
TLV - Threshold Limit Value  
TSCA - Toxic Substances Control Act  
TWA - Time Weighted Average  
V - Volume  
VOC - Volatile Organic Compound  
WHMIS - Workplace Hazardous Materials Information System