

Version 4.0 **REVISION DATE: 07/08/2012** Print Date 12/21/2013

SECTION 1 - PRODUCT IDENTIFICATION

Trade name Product code

THIN PATCH . TR5109650 :

COMPANY

Telephone

Euclid Chemical Company 19218 Redwood Road Cleveland, OH 44110 1-800-321-7628 Emergency Phone:

U.S. only: 1-800-424-9300 : International Users Call Collect: 1-703-527-3887

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Gray. Powder. Dust may irritate nose and throat. Dust irritating to the respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation Eyes	:	Dust may irritate nose and throat. Dust irritating to the respiratory tract. Direct contact may cause severe irritation. May cause mechanical irritation or abrasion, and possible chemical burns. May cause temporary injury.
Ingestion	:	May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.
Skin	:	May cause severe irritation. May cause dryness, cracking, irritation, and chemical burns. May produce cement dermatitis due to primary irritation from alkaline, hydroscopic and abrasive properties.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	40.0 - 70.0	
Portland cement	65997-15-1	30.0 - 60.0	
Calcium salt	7778-18-9	5.0 - 10.0	
/inyl Acetate copolymer	NJ TSRN# 51721300-5879P	1.0 - 5.0	



Version 4.0 REVISION DATE: 07/08/2012 Print Date 12/21/2013

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

 Inhalation
 : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

 Eye contact
 : Flush with water for at least 15 minutes while holding eye lids apart. Get medical

- attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point Method	:	Not available. Not available.
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	This product is not expected to burn under normal conditions of use.Use that which is appropriate to the surroundings.
Hazardous combustion products	:	Not available.
Protective equipment for firefighters	:	Not applicable. Product is not expected to burn.
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Dampen material with water to control dusting. Scoop up and transfer to appropriate container for disposal. Flush spill area with water.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of dust and contact with skin and eyes. Clean hands thoroughly after handling. Precautions also apply to emptied containers. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store in sealed containers in a cool, dry, ventilated warehouse location.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

An **RPM** Company



	Print Date 12/21/2013
:	Wear appropriate, properly fitted NIOSH/MSHA approved dust respirator where airborne concentrations are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
:	Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
:	Wear appropriate eye protection.Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
:	Prevent contact with shoes and clothing.
:	Use professional judgment in the selection, care, and use.Wear gloves, head coverings and full body clothing as necessary to prevent skin irritation. Washable or disposable clothing may be used. Do not take unwashed clothing home. Work clothes should be washed separately from other clothing and the washing machine rinsed thoroughly following use. Inform the launderer of the proper procedures. Store work clothes and street clothes separately to prevent contamination.
:	Use only in well ventilated areas. Provide maximum ventilation in enclosed areas.Use local exhaust when the general ventilation is inadequate.
	:

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Crystalline Silica (Quartz)/	14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable.
Silica Sand		OSHA TWA:	0.3 mg/m3	Total dust.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction.
Portland cement	65997-15-1	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	1 mg/m3	Respirable fraction.
Calcium salt	7778-18-9	ACGIH TWA:	10 mg/m3	
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	10 mg/m3	Inhalable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Powder
Color	: Gray
Odor	: None
рН	: Not available.
Vapour pressure	: Not available.
Vapor density	: Not available.

An **RPM** Company

Material Safety Data Shee	t	
THIN PATCH		EUCLID CHEMICAL
Version 4.0		Print Date 12/21/2013
REVISION DATE: 07/08/2012		
Melting point/range	: Not available.	
Freezing point	: Not available.	
Boiling point/range	: Not available.	
Water solubility	: Miscible	
Specific Gravity	: 2.6	
% Volatile Weight	: 0.0 %	
SECTION 10 - REACTIVITY	/ STABILITY	
Substances to avoid	: Not Applicable.	
Stability	: Material is stable under normal storage, ha	andling, and use.
Hazardous polymerization	-	0,
SECTION 12 - ECOLOGICA		
No Data Available		
SECTION 13 - DISPOSAL O	ONSIDERATIONS	
	regulated under RCRA. Dispose of in complian not incinerate.	ce with state and local regulations.
SECTION 14 - TRANSPOR	TATION / SHIPPING DATA	
CFR / DOT:		
Not Regulated		
TDG:		
Not Regulated		
IMDG:		
Not Regulated		
SECTION 15 - REGULATO	RY INFORMATION	
North American Inventories	:	
An RPM Company	4/6	TR5109650



I HIN PAICH				
Version 4.0 REVISION DATE: 07/08/2012			Print Date 12/21/2013	
All components are listed or exe This product or its components a		t from the TSCA inventory. listed on, or exempt from the Canadian	Domestic Substances List.	
U.S. Federal Regulations: SARA 313 Components	:	None present or none present in regula	ated quantities.	
SARA 311/312 Hazards : Acute Health Hazard Chronic Health Hazard				
OSHA Hazardous Components : Crystalline Silica (Quartz)/ Silica Portland cement Calcium salt		nd 14808-60-7 65997-15-1 7778-18-9		
OSHA Status: Considered hazardous based on the following criteria:	:	Irritant Carcinogen		
OSHA Flammability	:	Not Regulated		
Regulatory VOC (less water and exempt solvent) VOC Method 310		: 0 g/l : 0 %		
Chemical is listed as an IARC, N Crystalline Silica (Quartz)/ Silica				
U.S. State Regulations: MASS RTK Components	:	Crystalline Silica (Quartz)/ Silica Sand Portland cement Calcium salt Vinyl acetate Formaldehyde	14808-60-7 65997-15-1 7778-18-9 108-05-4 50-00-0	
Penn RTK Components	:	Crystalline Silica (Quartz)/ Silica Sand Portland cement Calcium salt	14808-60-7 65997-15-1 7778-18-9	
NJ RTK Components	:	Crystalline Silica (Quartz)/ Silica Sand Portland cement Calcium salt Vinyl Acetate copolymer	14808-60-7 65997-15-1 7778-18-9 NJ TSRN# 51721300-5879P	
Components under California Pro WARNING! Contains chemicals reproductive harm			ancer, birth defects and/or other	



Version 4.0 REVISION DATE: 07/08/2012 Print Date 12/21/2013

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	0
Reactivity	0
PPE	

0 = Minimum 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

Legend	
ACGIH - American Conference of Governmental Hygienists	PEL - Permissible Exposure Limit
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act	RCRA - Resource Conservation and Recovery Act
DOT - Department of Transportation	RTK - Right To Know
DSL - Domestic Substance List	SARA - Superfund Amendments and Reauthorization Act
EPA - Environmental Protection Agency	STEL - Short Term Exposure Limit
HMIS - Hazardous Materials Information System	TLV - Threshold Limit Value
IARC - International Agency for Research on Cancer	TSCA - Toxic Substances Control Act
MSHA - Mine Safety Health Administration	TWA - Time Weighted Average
NDSL - Non-Domestic Substance List	V - Volume
NIOSH - National Institute for Occupational Safety and Health	VOC - Volatile Organic Compound
NTP - National Toxicology Program	WHMIS - Workplace Hazardous Materials Information System
OSHA - Occupational Safety and Health Administration	