

M A T E R I A L S A F E T Y D A T A S H E E T

I. P R O D U C T I D E N T I F I C A T I O N:

Prepared for: Visual Pollution Tech, Inc. P.O. Box 12833, Scottsdale, AZ 85267

Info Phone: 480-657-9183 Chem Emergency 800-255-3924 Prepared 4/14/97 By T.W.Smoot

Product Name: Prmakote Product Code: 333

II. H A Z A R D O U S I N G R E D I E N T S :

Parafinic, naphthanic solvent, Combustible liquid	OSHA/PEL	max %
SARA 211/312 "Fire hazard" ; Contains no chemicals subject to SARA 302 or 313 reporting.	100 ppm for 8 hours	<90.0

III. H E A L T H H A Z A R D I N F O R M A T I O N:

Primary Routes of Entry: ☐ Inhalation ☐ Ingestion ☒ Skin ☒ Eyes

Effects of Over Exposure: EYE CONTACT: Can cause irritation; tearing; redness.

SKIN CONTACT: Prolonged contact can cause drying, defatting & may cause dermatitis.

INHALATION: ND ; INGESTION: ND

HMIS HAZARD INDEX:

HEALTH - 1

FLAMMABILITY - 1

REACTIVITY - 0

IV. E M E R G E N C Y F I R S T A I D:

INGESTION: get medical attention-only induce vomiting on advice from Physician ; INHALATION: Remove to fresh air.

EYE CONTACT: Flush well with water for at least 15 minutes, get medical help. SKIN: Rinse well with water.

V. F I R E & E X P L O S I O N D A T A:

Flash Point: > 140 ° F Test Methods: T.C.C.

Flammability Limits in Air, % by Vol.: Lower 0.7 : Upper 7

Extinguishing Media: Water Spray, dry chemical, CO2

Special Fire Fighting Procedures: Treat as combustible liquid. Self contained breathing apparatus.

Unusual Fire Fighting Hazard: Treat as NFPA Class IIIA Combustible liquid.

VI. A C C I D E N T A L R E L E A S E M E A S U R E S:

Dam up and collect for possible reuse. Wash area with water.

VII. H A N D L I N G & S T O R A G E:

Keep container closed when not in use.

VIII. E X P O S U R E C O N T R O L / P R O T E C T I O N:

For extended usage, wear chemically resistant gloves; work in well ventilated area; eye protection is recommended.

IX. P H Y S I C A L D A T A:

Boiling Point: > 350 F

pH, neat: NA

Specific Gravity, (HOH=1): 0.97

Ph, 1% Sol: NA

Vapor Pres.: MMHg @ 20C: ND

Solubility: dispersible

Vapor Density: (Air=1): ND

Evaporation Rate: ND

% Volatiles/volume: NA

Description/odor: Clear, with slight petroleum like odor

X. S T A B I L I T Y A N D R E A C T I V I T Y:

Product is stable. ; Hazardous Polymerization: will not occur ; Conditions to avoid: NA

XI. T O X I C O L O G I C A L I N F O R M A T I O N:

Not determined; not known to be toxic.

XII. E C O L O G I C A L I N F O R M A T I O N: ND

XIII. D I S P O S A L I N F O R M A T I O N:

Flush to sewer, according to Local, State & Federal Regulations.

XIV. T R A N S P O R T I N F O R M A T I O N:

DOT HAZARD CLASSIFICATION: Combustible Liquid, not flammable.

XV. R E G U L A T O R Y I N F O R M A T I O N: SARA 311/312 "Fire Hazard"

XVI. A D D I T I O N A L I N F O R M A T I O N: NA

The information contained herein is based on data available to us and is believed to be correct. We make no warranty, however, expressed or implied regarding the accuracy of these data or the results obtained from the use thereof.