



MATERIAL SAFETY DATA SHEET

Page 1 of 7

HE208 - WET PATCH ROOF LEAK REPAIR

1. Product And Company Identification			
<u>Supplier</u> HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com		<u>Manufacturer</u> HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com	
<u>Supplier Emergency Contacts & Phone Number</u> CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666		<u>Manufacturer Emergency Contacts & Phone Number</u> CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666	
 Issue Date: 05/20/2011 Product Name: HE208 - WET PATCH ROOF LEAK REPAIR Product Code: HE208			
2. Composition/Information On Ingredients			
Ingredient Name		CAS Number	Percent Of Total Weight
1,2,4-trimethylbenzene		95-63-6	1 - 5
aromatic petroleum distillates		64742-95-6	1 - 5
petroleum asphalt		8052-42-4	30 - 60
attapulgate		12174-11-7	5 - 15
calcium carbonate		1317-65-3	15 - 35
cellulose fiber		9004-34-6	5 - 15
silica, quartz		14808-60-7	0.1 - 1
stoddard solvent		8052-41-3	10 - 30
Substances in this product have been pre-registered in accordance with the REACH Regulation - (EC) No. 1907/2006. See Section 15 for additional information.			
EMERGENCY OVERVIEW			
CAUTION! Combustible Liquid. Central nervous system depressant. Vapor may cause light-headedness, headache, nausea, loss of coordination and respiratory tract irritation. Causes skin irritation.			
Appearance/Odor: Black paste, strong petroleum solvent odor			
3. Hazards Identification			
<u>Primary Routes(s) Of Entry</u> Inhalation			
<u>Eye Hazards</u> May cause eye irritation (burning, tearing, redness or swelling).			



HE208 - WET PATCH ROOF LEAK REPAIR

3. Hazards Identification - Continued

Skin Hazards

May cause skin irritation and contact dermatitis upon prolonged contact. Dermal sensitization may occur from repeated and prolonged exposures.

Ingestion Hazards

May be harmful if swallowed. May cause gastric distress, vomiting and diarrhea.

Inhalation Hazards

Exposure to vapors may cause respiratory tract irritation. Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.

Chronic/Carcinogenicity Effects

This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 (Toxicological Information) for more details.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

Remove contaminated clothing and shoes. Wash affected areas with soap and water.

Ingestion

Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim. Call a physician or poison control center immediately.

Inhalation

Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately.

5. Fire Fighting Measures

Flash Point: >105 °F >40.5 °C

Flash Point Method: Setaflash

Lower Explosive Limit: 0.9

Upper Explosive Limit: 6.0

Fire And Explosion Hazards

Combustible Liquid. Vapors are heavier than air and may spread long distances and ignite. Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Extinguishing Media

Chemical foam, carbon dioxide (CO₂), or dry chemical. Do not use direct stream of water.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Collect and dispose in accordance with applicable regulations.

7. Handling And Storage

Handling And Storage Precautions

Keep away from ignition sources. Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Do not handle or store near heat, sparks, flame, strong oxidants or strong acids. Use only with adequate ventilation. Ground all

HE208 - WET PATCH ROOF LEAK REPAIR

7. Handling And Storage - Continued

Handling And Storage Precautions - Continued

containers.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

Use with chemical-protective gloves to prevent skin contact.

Respiratory Protection

The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

Ingredient(s) - Exposure Limits

1,2,4-trimethylbenzene

ACGIH TLV-TWA 25 ppm

aromatic petroleum distillates

OSHA PEL-TWA 500 ppm

petroleum asphalt

ACGIH TLV-TWA 0.5 mg/m3 (inhalable fraction, as benzene-soluble aerosol)

calcium carbonate

OSHA PEL-TWA 15 mg/m3 (total dust)

OSHA PEL-TWA 5 mg/m3 (respirable dust)

cellulose fiber

ACGIH TLV-TWA 10 mg/m3

silica, quartz

ACGIH TLV-TWA 0.025 mg/m3

OSHA PEL-TWA 30mg/m3 / (%SiO₂+2) (total dust)

OSHA PEL-TWA 10 mg/m3/ (%SiO₂+2) (respirable dust)

stoddard solvent

ACGIH TLV-TWA 100 ppm

OSHA PEL-TWA 500 ppm

9. Physical And Chemical Properties

Appearance

Black Paste

Odor

Strong Petroleum Solvent Odor

Chemical Type: Mixture

Physical State: Solid

Boiling Point: 310-400 °F

Specific Gravity: 1.14

Percent Volatiles: 22

HE208 - WET PATCH ROOF LEAK REPAIR

9. Physical And Chemical Properties - Continued

Odor - Continued

Vapor Pressure: 2@68°F

Vapor Density: >1

pH Factor: not applicable

Solubility: insoluble in water

Evaporation Rate: <1

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Incompatible Materials

Avoid contact with strong oxidizing agents and acids.

Hazardous Decomposition Products

Toxic and irritating gases, vapors or fumes, carbon monoxide (CO), carbon dioxide (CO₂).

11. Toxicological Information

Chronic/Carcinogenicity

IARC has concluded that the following chemicals in this product are carcinogenic to humans (Group 1): silica, quartz

ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz

NTP has listed the following chemicals in this product as known human carcinogens: silica, quartz

Risk of cancer depends on duration and level of exposure to this product as a dust.

Miscellaneous Toxicological Information

Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

Ingredient(s) - Toxicological Data

1,2,4-trimethylbenzene

LD50 (oral, rat): 5000 mg/kg

LC50 (rat): 18 g/m³ (4-hour exposure)

aromatic petroleum distillates

LD50 (oral, rat): 2900 mg/kg

calcium carbonate

oral-rat LD50: 6450 mg/kg

cellulose fiber

LD50 (oral, rat): >2000 mg/kg

LC50 (rat): >5800 mg/m³ (4-hour exposure)

silica, quartz

iv-rat LD50: 500 mg/kg bw/Quartz (10-200 um)

stoddard solvent

oral-rat LD50: >5000 mg/kg

dermal-rabbit LD50: >3000 mg/kg

inhal-rat LC50: >5500 mg/m³ (880 ppm)

inhal-rat LC50: >1300 ppm

12. Ecological Information

No specific information available.

HE208 - WET PATCH ROOF LEAK REPAIR

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Ground or Water Domestic Voyage

Not restricted if shipped in containers < 450L (119 gallons)

Restricted if shipped in containers > 450L (119 gallons)

US NA1993, Combustible liquid, n.o.s., (Petroleum Distillates mixture), Combustible liquid, III

Canada UN1999, Tars liquid, 3, III

Unless departs > flash point:

Both UN3256, Elevated Temperature liquid, flammable, n.o.s., (Petroleum Distillates mixture), 3, III

IMDG IMDG Code 2.3.2.5 - exempted from marking, labeling & testing of packages

IATA UN1999, Tars liquid, 3, III

DOT (Pictograms)



15. Regulatory Information

U.S. Regulatory Information

Asphalt may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.

Ingredient(s) - U.S. Regulatory Information

1,2,4-trimethylbenzene

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

Ingredient(s) - State Regulations

1,2,4-trimethylbenzene

New Jersey - Workplace Hazard

New Jersey - Environmental Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

aromatic petroleum distillates

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

petroleum asphalt

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

attapulgit

California - Proposition 65

HE208 - WET PATCH ROOF LEAK REPAIR

15. Regulatory Information - Continued

Inredient(s) - State Regulations - Continued

calcium carbonate

Pennsylvania - Workplace Hazard

cellulose fiber

Pennsylvania - Workplace Hazard

silica, quartz

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

California - Proposition 65

Massachusetts - Hazardous Substance

stoddard solvent

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: B3 - Combustible Liquid, D2A - Very Toxic

Inredient(s) - Canadian Regulatory Information

1,2,4-trimethylbenzene

WHMIS - Ingredient Disclosure List

silica, quartz

WHMIS - Ingredient Disclosure List

stoddard solvent


WHMIS - Ingredient Disclosure List

European Union (EU) Regulatory Information

REACH Pre-registration Information:

Substance (CAS#)	Reference Number
Asphalt (8052-42-4)	05-2114366982-36-0000
Stoddard Solvent (8052-41-3)	05-2114367025-53-0000
Calcium Carbonate (1317-65-3)	05-2114501824-55-0000
Cellulose (9004-34-6)	05-2114366989-22-0000
1,2,4-Trimethylbenzene (95-63-6)	05-2114501851-58-0000
1,3,5-Trimethylbenzene (108-67-8)	05-2114501879-40-0000
Xylene (1330-20-7)	05-2114367081-55-0000
Attapulgate (12174-11-7)	NA-Naturally Occurring Substanc

WHMIS - Canada (Pictograms)



HE208 - WET PATCH ROOF LEAK REPAIR

NFPA	HMIS
	HEALTH 2
	FLAMMABILITY 2
	REACTIVITY 0
	PERSONAL PROTECTION

16. Other Information

Revision/Preparer Information

This MSDS Supersedes A Previous MSDS Dated: 06/10/2010

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).