Page 1

Date of preparation: 06/14/11 3915000-1

## **SECTION I**

No.

Manufacturer : W. R. MEADOWS⊚, INC. - H M I S -

Address : 300 Industrial Dr. | Health : 1 |
: Hampshire, IL 60140 | Flammability : 2 |
| Reactivity : 0 |

Telephone # : (847) 683-4500 | Reactivity : 0 | Personal Protection : 1

Emergency # : 1-800-424-9300 Chemtrec

(Hazard Rating:0=Least,1=Slight,2=Moderate,3=High,4=Extreme,\*=Chronic)

Product Class : DIVISION 3 Mfg. code I.D. : 3915000-1

Trade Name : DUOGARD® VOC FORM RELEASE AGENT

# SECTION II-A HAZARDOUS COMPONENTS

		% by	SARA	VAPOR PRESSURE	LEL
No. Component	CAS#	Weight	313	(mm Hg @ 20 C)	(@ 25 C)
1. Petroleum Oil Base Stock	64742-54-7	90-100	NO	< 0.1	0.90

<sup>&</sup>gt;> None of the components of this product are recognized as carcinogenic.

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313".

# SECTION II-B OCCUPATIONAL EXPOSURE LIMITS

OSHA

PEL/TWA PEL/CEILING PEL/STEL SKIN TLV/TWA TLV/CEILING TLV/STEL SKIN 5 mg/m³\* N/E N/E NO 100 mg/m³\*+ N/E 10 mg/m3\* NO

\*Mineral Oil Mist in air. N/E= Not Established + = Aerosol / Vapor

Skin absorption may contribute to the overall exposure to this material. Take appropriate measures to prevent skin contact.

## SECTION III PHYSICAL DATA

 Boiling Point
 : 347 degrees F.
 % Volatile by volume
 : N/A (Theoretical)

 Evaporation Rate
 : < 1 (ether = 1)</td>
 % Volatile by weight
 : 27.8 (Theoretical)

 Vapor Density
 : > 1 (air = 1)
 Weight per gallon
 : 7.4 (Theoretical)

 VOC
 : 268 g/L

# SECTION IV HEALTH INFORMATION

EYE CONTACT: This product may cause slight eye irritation. Corneal injury is unlikely.

**SKIN CONTACT:** Exposure may cause mild skin irritation. Prolonged or repeated contact may cause redness, drying, burning, and cracking of the skin. Persons with pre-existing skin disorders may be more susceptible to the effects of this material. Irritation is unlikely after brief contact but may be irritating after prolonged contact.

**INHALATION:** Exposure may produce irritation to the nose, throat, respiratory tract, and other mucous membranes.

INGESTION: May cause irritation of the gastrointestinal tract. Ingestion may cause pulmonary injury.

**SIGNS AND SYMPTOMS:** Symptoms of eye irritation include pain, tearing, reddening, and swelling. Symptoms of skin irritation include reddening, swelling, rash, and redness. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. Symptoms of gastrointestinal irritation include sore throat, abdominal pain, nausea, vomiting, and diarrhea.

AGGRAVATED MEDICAL CONDITIONS: Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure to this product.

OTHER HEALTH EFFECTS: None known.

## SECTION V EMERGENCY AND FIRST AID PROCEDURES

**EYE CONTACT:** If irritation or redness develops, move victim away from exposure source and into fresh air. Flush eyes with water for fifteen minutes. If symptoms persist, seek medical attention.

**SKIN CONTACT:** Remove contaminated shoes and clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists seek medical attention.

**INHALATION:** If respiratory symptoms develop, move victim away from exposure source and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

**INGESTION**: Do not induce vomiting. Vomiting will cause further damage to the throat. Dilute by giving water or milk to drink if the victim is conscious. Consult a physician, hospital, or poison control center and/or transport to an emergency facility.

Page 2

Date of preparation: 06/14/11 3915000-1

#### **SECTION VI** FIRE AND EXPLOSION HAZARDS

FLAMMABILITY CLASSIFICATION

- NFPA: Combustible Liquid - Class IIIA - DOT: Not Regulated by D.O.T.

FLASH POINT: 195 degrees F.

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical, or carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS: Clear fire area of unprotected personnel. Do not enter confined fire space without helmet, face shield, bunker coat, gloves, rubber boots, and a positive pressure NIOSH approved self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure.

#### **SECTION VII** REACTIVITY

**STABILITY: Stable** 

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS AND MATERIALS TO AVOID: Avoid oxidizing materials.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may yield Carbon Dioxide, Carbon Monoxide, and/or incomplete combustion products. Do not breathe smoke or fumes. Wear appropriate protective equipment.

#### SECTION VIII **EMPLOYEE PROTECTION**

RESPIRATORY PROTECTION: Use ventilation as required to control vapor concentrations - at least 10 air changes per hour are recommended for good general room ventilation. If exposure exceeds the PEL/TLV, use the appropriate NIOSH approved respirator.

PROTECTIVE CLOTHING: Wear safety glasses, goggles, or a splash shield to prevent eye contact. Contact lenses should not be worn. Wear appropriate gloves and protective clothing to prevent contact with skin and clothing.

ADDITIONAL PROTECTIVE MEASURES: Eye wash fountains and safety showers should be available for use in an emergency.

#### SECTION IX ENVIRONMENTAL PROTECTION

SPILL OR LEAK PROCEDURES: LARGE SPILLS>> Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak only if safe to do so. Dike and contain. If vapor cloud forms, water fog may be used to suppress; contain run-off. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; dispose of flush solutions as above. SMALL SPILLS>> Take up with an absorbent material and place in non-leaking containers; seal tightly for proper disposal. WASTE DISPOSAL: Observe all Federal, State and local regulations regarding proper disposal.

#### **SECTION X** ADDITIONAL PRECAUTIONS

Containers can contain product residues even when empty. Wash with soap and water before eating, drinking, smoking or using toilet facilities

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described within.

Date of preparation: 06/14/11 3915000-1 DUOGARD VOC FORM RELEASE AGENT