



# SAFETY DATA SHEET

## SECTION 1 - PRODUCT IDENTIFICATION

**Product:** MASCOBOND LO-MOD (PART B)  
**Revision Date:** 9/3/2015

**Manufacturer:** Masons Supply Company (MASCO)  
2637 SE 12th Avenue  
Portland, OR 97202  
TEL (503) 234-4321  
FAX (503) 234-5606

## SECTION 2 - HAZARDS IDENTIFICATION

### Emergency Overview

Amber. Liquid. May cause slight irritation to the respiratory system. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

### Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.  
Eyes : Vapors or liquid may cause tearing, blurred vision, severe irritation, and possible chemical burns.  
Ingestion : May cause gastrointestinal irritation, nausea, and vomiting. May cause chemical burns to stomach, mouth, nose, and throat.  
Skin : May cause itching, reddening, inflammation. May cause severe burns, blistering and skin damage. May cause sensitization resulting in irritation, itching and redness. May cause a rash.

### Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

### Chronic Health Effects

May cause sensitization by contact. Prolonged skin contact may cause irritation, burns or dermatitis. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. May aggravate persons sensitized to amines. Diethylenetriamine is a skin and eye irritant. Prolonged and repeated exposure can cause skin sensitization, dermatitis, asthma. Repeated inhalation of nonyl phenol may cause lung damage. Repeated skin contact with nonyl phenol may cause skin irritation and dermatitis. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

## SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
4-Nonylphenol	84852-15-3	40.0 - 70.0
Epoxy curing agent	NJ TSRN# 51721300-5477P	15.0 - 40.0
Poly(oxypropylene) diamine	9046-10-0	10.0 - 30.0
Diethylenetriamine	111-40-0	7.0 - 13.0
Bisphenol A	80-05-7	3.0 - 7.0
Tris(dimethylaminomethyl)phenol	90-72-2	3.0 - 7.0

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : > 200 °F, > 93 °C
- Method : Setaflash Closed Cup
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Smoke, fumes. Nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Vapor concentrations in enclosed areas may ignite explosively. Empty containers may contain ignitable vapors.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not smoke, weld, generate sparks, or use flame near container. Do not use in confined or poorly ventilated areas. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Store under dry warehouse conditions away from heat and all ignition sources.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Wear NIOSH/MSHA approved vapor respirator with appropriate cartridge when the vapor concentration is expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing. Use rubber apron and overshoes.
- Protective measures : Inspect and replace equipment at regular intervals. Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Diethylenetriamine	111-40-0	ACGIH TWA:	1 ppm	

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Liquid
- Color : Amber
- Odor : Amine
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.

Water solubility : Negligible  
 Specific Gravity : 1.20  
 % Volatile Weight : 47.4 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Oxidizing agents.Epoxies.Isocyanates.Acids.  
 Stability : Material is stable under normal storage, handling, and use.  
 Hazardous polymerization : Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Diethylenetriamine, CAS-No.: 111-40-0  
 Acute oral toxicity (LD-50 oral) 1,080 mg/kg ( Rat ) 2,330 mg/kg ( Rat )  
 Bisphenol A, CAS-No.: 80-05-7  
 Acute oral toxicity (LD-50 oral) 4,100 mg/kg ( Rat ) 3,300 mg/kg ( Rat ) 5,280 mg/kg ( Mouse ) 4,100 mg/kg ( Mouse ) 2,500 mg/kg ( Mouse )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**CFR / DOT:**

UN1760, Corrosive liquids, n.o.s. (Aliphatic Amine), 8, PG III

**TDG:**

UN1760, CORROSIVE LIQUID, N.O.S. (Aliphatic Amine), 8, PG III

**IMDG:**

UN1760, CORROSIVE LIQUID, N.O.S. (Aliphatic Amine, Nonylphenol), 8, PG III, MARINE POLLUTANT

**Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : Bisphenol A 80-05-7

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components :

Diethylenetriamine 111-40-0

Bisphenol A 80-05-7

OSHA Status: Considered : Irritant  
hazardous based on the : Corrosive  
following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 569 g/l  
exempt solvent)

VOC Method 310 : 47 %

**U.S. State Regulations:**

MASS RTK Components : Diethylenetriamine 111-40-0  
Bisphenol A 80-05-7

Penn RTK Components : 4-Nonylphenol 84852-15-3  
Epoxy curing agent NJ TSRN# 51721300-5477P  
Poly(oxypropylene) diamine 9046-10-0  
Diethylenetriamine 111-40-0  
Bisphenol A 80-05-7  
Tris(dimethylaminomethyl)phenol 90-72-2

NJ RTK Components : 4-Nonylphenol 84852-15-3  
Epoxy curing agent NJ TSRN# 51721300-5477P  
Poly(oxypropylene) diamine 9046-10-0  
Diethylenetriamine 111-40-0  
Bisphenol A 80-05-7

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:  
None known.

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	2
Flammability	1
Reactivity	1
PPE	

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**DISCLAIMER**

**Masons Supply Company** believes that the information on this SDS was obtained from reliable sources. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, **Masons Supply Company** does not assume any responsibility and expressly disclaims liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS information may not be applicable. Information is correct to the best of our knowledge at the date of the SDS publication.

**LEGEND**

- ACGIH - American Conference of Governmental Hygienists
- CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration
- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- RTK - Right To Know
- SARA - Superfund Amendments and Reauthorization Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System