



# MASCOSEAL ACRYLIC GOLD

P.O. Box 42367 Portland, OR 97242 503-234-4321 FAX: 503-234-5606  
6018-234<sup>th</sup> St. SE Woodinville, WA 98072 425-487-6161 FAX: 425-402-3676

## **BENEFITS:**

- 100% Non-Yellowing
- Excellent Breatheability
- Makes Surfaces Self-Cleaning With Rainfall
- Protects Against Damaging Effects of Freeze/Thaw Cycles, Deicing Chemicals & Airborne Contaminants



**Enhances natural beauty of  
stone, exposed aggregate and  
concrete...**

**MASCOSEAL ACRYLIC GOLD**

# MASCOSEAL ACRYLIC GOLD

---

## DESCRIPTION

A methyl methacrylate, water-clear plexiglass shield for exposed aggregate, precast and concrete formulated with scientifically selected polymers for moisture repellence and high resistance to abrasion. Will not yellow. MASCOSEAL ACRYLIC GOLD when applied to cured concrete in two thin coats enhances the look of new and old concrete bringing out the beauty of exposed aggregate. It is commonly referred to as a "wet look" sealer that provides UV light resistance in a fast dry solvent formula.

## USAGE

Chemically seals:

- Exposed aggregate
- Precast
- Concrete

## APPLICATION

### *Surface Preparation:*

Test panels should be made on specific jobs to ensure use of proper sealer and to determine the number of coats required. Surface must be clean, dry, structurally sound and free of foreign matter such as grease, oil and dirt. Defective mortar and open joints should be pointed. Cracks, expansion joints, and spalling should be repaired before sealing.

### *Method:*

Spray or roll.

### *Application:*

Allow exposed aggregate and colored concrete to cure a minimum of 7 days prior to application. Spray 1 light coat, avoiding puddling. Allow 1<sup>st</sup> coat to dry prior to application of 2<sup>nd</sup> coat to avoid trapping solvents.

## PACKAGING

1 gal / 3.8 L units (6/case)  
5 gal / 18.9 L pails  
55 gal / 208 L drums

## COVERAGE

Exposed aggregate, concrete, & precast (above grade):

200-300 sq ft / gal  
4.9 – 7.4 sq m / L

## CLEANUP

Sprayers and other application equipment can be cleaned with Masco CITRI-CLEAN.

## COMPLIANCES

ASTM-C-1315:

Type 1  
Class A

## LIMITATIONS

- Should be applied at 40°F (4°C) or above.
- Never apply to frozen concrete even if the atmospheric temperature has gone up to 50-60°F (10-16°C).
- Protect glass, ceramic, and aluminum from overspray.
- Not for continual immersion in water or around pools and fountains. Product can cause slipperiness when wet.
- Test panels should be made on specific jobs and left for the amount of time specified by the architect to ensure use of proper sealer and to determine the number of coats required.
- Technical Bulletin 4312: If sealers are applied too soon to colored concrete, they may turn milky under some circumstances. Sealers are most reliably applied to colored concrete that has cured a minimum of 7 days.
- Test before application to colored concrete.
- Not recommended for non porous surfaces, i.e. brick, stone, slate, masonry, etc.
- Do not use in areas subject to moisture vapor transmission.

## CAUTION

- Contains combustible solvent
- Keep away from sources of ignition
- Use with adequate ventilation

**DISCLAIMER OF WARRANTIES AND LIMITATIONS OF LIABILITY:** MASONS SUPPLY CO. (Seller) warrants that if any goods supplied prove defective in workmanship or material, that Seller shall replace them or refund their purchase price. THIS WARRANTY IS MADE IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS WHICH ARE HEREBY DISCLAIMED. IT IS UNDERSTOOD AND AGREED THAT BUYER'S SOLE REMEDY, AND THEREFORE SELLER'S LIABILITY, WHETHER IN CONTRACT, TORT, UNDER ANY WARRANTY, IN NEGLIGENCE, OR OTHERWISE SHALL BE LIMITED TO THE RETURN OF THE PURCHASE PRICE PAID BY PURCHASER OR REPLACEMENT OF ANY DEFECTIVE GOODS SOLD BY SELLER AND UNDER NO CIRCUMSTANCES SHALL SELLER BE LIABLE FOR SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES. THE PRICE STATED FOR THE GOODS IS A CONSIDERATION IN LIMITING SELLER'S LIABILITY. Before application, the User shall determine the suitability of the product for his intended use, and User assumes all risks and liabilities whatsoever in connection therewith. The terms of this paragraph may not be orally modified. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE FACE HEREOF.

**For technical assistance,  
call a Masons Supply  
Company representative  
at: 503-234-4321**