



# Material Safety Data Sheet

EMERGENCY PHONE: 1 – 800- 424-9300 (CHEMTREC)  
INFORMATION PHONE: 1 – 800 – 537-6216

## I. CHEMICAL PRODUCT AND COMPANY DATA

PRODUCT: MASCOBOND HI-MOD GEL, COMPONENT B  
CHEMICAL FAMILY: AMINE MIXTURE  
REVISION DATE: 2/02  
SUPPLIER: MASONS SUPPLY COMPANY

## II. COMPOSITION / INFORMATION ON INGREDIENTS

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### EXPOSURE LIMITS

<u>INGREDIENT</u>	<u>CAS. NO.</u>	<u>TLV</u>	<u>STEL</u>	<u>PEL</u>	<u>CONTENT</u>
MODIFIED AMINE	*	N/E	N/E	N/E	>50%
PETROLEUM DISTILLATE	68477-31-6	N/E	N/E	N/E	<15%
ALIPHATIC AMINE	112-57-2	N/E	N/E	N/E	<8%
AMINO PHENOL	90-72-2	N/E	N/E	N/E	<3%
COLLOIDAL SILICA	67762-90-7	N/E	N/E	N/E	<10%

\* Specific chemical identity of this component is being held as trade secret information in accordance with CFR 1910.1200  
*N/E=NOT ESTABLISHED*

## III. HAZARDS IDENTIFICATION

HMIS Hazard Rating No. 3 (HIGH)

PRIMARY ROUTE OF ENTRY: *INHALATION, DERMAL, EYES*

EFFECTS OF OVER EXPOSURE:

**INHALATION:**

Vapors/mist may be corrosive to upper respiratory tract. Repeated or prolonged exposure can result in lung damage. Lung damage may be evidenced by shortness of breath and may be accompanied by chronic cough.

**EYES:**

Product may cause irritation to the eyes. Corrosive to the eyes and may cause severe damage including blindness.

**SKIN CONTACT:**

Corrosive to the skin. May cause skin sensitization.

**SKIN ABSORPTION:**

No known information available.

**INGESTION:**

Not expected to be a relevant route of exposure. However, may cause permanent damage to mouth, throat and stomach.

**CHRONIC:** Repeated exposure may cause skin sensitization, or sensitization to the respiratory tract and development of an asthmatic reaction to future exposure. Preexisting eye, skin, and respiratory disorders may be aggravated by exposure of this product.

#### **IV. FIRST AID MEASURES**

**INHALATION:** Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped, administer artificial respiration. Seek medical attention.

**EYES:** Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.

**SKIN:** Immediately remove contaminated clothing. Wash thoroughly with soap and water for at least 15 minutes. If irritation occurs, get medical attention. Do not re-use clothing until thoroughly cleaned.

**INGESTION:** Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Give one glass of water unless victim is drowsy, convulsing or unconscious. Seek medical attention.

#### **V. FIRE FIGHTING METHODS**

**HMIS Hazard Rating No. 1 (Slight)**

**Flash Point:** >200° F

**METHOD:** SETAFLASH

**AUTO-IGNITION TEMP.:** Not available

**LIMITS OF FLAMMABILITY:** LEL: Not available UEL: Not available

**EXTINGUISHING MEDIA:** Use water fog, dry chemical or CO<sub>2</sub>.

**SPECIAL FIRE FIGHTING PROEDURES AND PRECAUTIONS:** Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure NIOSH approved self-contained breathing apparatus. Cool fire exposed containers with water.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup, which could result in container rupture. Delayed lung damage can be experienced after exposure to combustion product. Nitrogen oxides and nitrogen containing organic compounds may be released upon combustion.

#### **VI. ACCIDENTAL RELEASE MEASURES**

**ACTION TO TAKE FOR SPILLS/ LEAKS:** Danger. Corrosive. Prevent all bodily contact with spilled material. Clean up personnel must be equipped with self-contained breathing apparatus, rubber gloves and protective clothing. Dike and contain the spill. Soak up residue with an absorbent such as clay, sand or other suitable material. Dispose of the absorbent material in accordance with federal, state and local regulations. Residual resin may be removed with hot soapy water.

**WASTE DISPOSAL METHOD:** Dispose in compliance with federal, state and local regulations.

#### **VII. HANDLING AND STORAGE**

**HANDLING:**  
Keep away from open flames and high temperatures.

**STORAGE:**  
Store in ventilated area



**SKIN ABSORPTION:** No information available.

**INGESTION:** Not expected to be route of entry. May cause permanent damage to mouth, throat, and stomach.

**LD(50) ORAL**

<u>CAS. NO.</u>	
90-72-2	>2169 mg/kg (rat)
112-57-2	3.99 g/kg (rat)
68477-31-6	2,622 mg/kg (rat)

**CHRONIC:** Product does not contain chemicals considered to be carcinogenic by NTP, IARC, ACGIH, or OHSA.

## **XII. ECOLOGICAL INFORMATION**

Marine Pollutant: NL

(NL = Not Listed; P = Moderate; PP = Severe; ND = Not Determined)

## **XIII. DISPOSAL CONSIDERATIONS**

Dispose in a manner which complies with local, state and federal regulations.

## **XIV. TRANSPORT INFORMATION**

**DOT SHIPPING NAME:** POLYAMINES, LIQUID, CORROSIVE, N.O.S., (ALKALINE AMINE)

**DOT HAZARD CLASS:** CLASS 8 (CORROSIVE LIQUID), PGIII

**DOT PLACARD:** CORROSIVE

**OTHER REQUIREMENTS:** UN1760, CLASS 60

## **XV. REGULATORY INFORMATION**

COMPONENTS ARE LISTED ON THE EPA/TSCA

**TITLE III SECTION 302:**

**TITLE III SECTION 311/312:**

**TITLE III SECTION 313:**

INVENTORY OF CHEMICAL SUBSTANCES

No reportable materials.

Health hazard: Immediate

Physical hazard: Fire

No reportable materials.

## **XVI. OTHER INFORMATION**

Information contained in this MSDS refers only to the specific material designated and does not relate to any process or to use with any other materials. This information is based on data believed to be reliable as of the date hereof. It is furnished without warranty of any kind express or implied. Since actual use is beyond our control, no guarantee, express or implied, and no liability is assumed by MASONS SUPPLY COMPANY in conjunction with the use of this information. Nothing herein is to be construed as a recommendation to infringe any patents.